

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65


5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>AMOCO PRODUCTION COMPANY</b>	8. Farm or Lease Name <b>Likins Gas Com "A"</b>
3. Address of Operator <b>501 Airport Drive, Farmington, New Mexico</b>	9. Well No. <b>1A</b>
4. Location of Well UNIT LETTER <b>J</b> <b>1650</b> FEET FROM THE <b>South</b> LINE AND <b>1640</b> FEET FROM THE <b>East</b> LINE, SECTION <b>34</b> TOWNSHIP <b>30N</b> RANGE <b>9W</b> NMPM.	10. Field and Pool, or Wildcat <b>Blanco Mesaverde</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>5699' GL</b>	12. County <b>San Juan</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <b>Spud &amp; set casing</b> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12-1/4" hole 5:00 pm, 10-9-76 and drilled to 278' with boulders from 55-65'.  
Set 9-5/8" casing at 278' with 280 sacks Class "B" cement with 2% CaCl2 on 10-9-76.  
Circulated cement. Waited on cement to set, tested casing, manifold and blowout  
preventer with 800 psi OK. Reduced hole to 8-3/4" and continued drilling.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u><i>E. Svoboda</i></u>	TITLE <u>Area Adm. Supvr.</u>	DATE <u>10-13-76</u>
Original Signed by A. R. Vender		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		