

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

87 078200

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

W. M. Riddle

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

Blanco Manzanita11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**NW/4 NW/4 Section 24,
T-30-N, R-10-W**

12. COUNTY OR PARISH 13. STATE

San Juan**New Mexico****SUNDRY NOTICES AND REPORTS ON WELLS**
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

301 Airport Drive, Farmington, New Mexico 874014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**925' FWL & 790' FWL, Section 24, T-30-N, R-10-W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6201' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING


SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) **Spud and set casing****X**(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 12-1/4" hole 6:30 p.m., 10-23-76 and drilled to 243'. Set 9-5/8" surface casing at 240' with 200 sacks Class "B" cement with 2% CaCl₂ on 10-24-76. Cement circulated. Tested blowout preventer, manifold and casing to 800 psi OK. Reduced hole to 8-3/4" and continued drilling to 3300'. Set 7" casing at 3300' with 575 sacks Class "B" cement with 6% Gel and 2 pounds medium Tuf Plug per sack followed by 50 sacks Class "B" cement on 10-27-76. Cement did not circulate. Continued drilling to TD of 5400'. Set 4-1/2" liner from 3096 to 5400'. Ran 20 barrels chemical wash and cemented liner with 200 sacks Class "B" 30:50 Poz, 6% Gel, 2 pounds medium Tuf Plug per sack and 0.2% friction reducer followed by 75 sacks Class "B" 30:50 Poz, 6% Gel on 10-31-76. Reversed out 10 barrels cement.



RECEIVED

NOV 8 1976

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Superintendent

DATE

November 5, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.