UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	NM	-	20313			1.5
6.	IF INDIAN, A	\LL	OTTEE O	R TRI	BE N	AMÉ

SUNDRY NOT	TICES AND	REPORTS	ON	WELLS
------------	-----------	---------	----	-------

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

8. FARM OR LEASE NAME gas well \mathbf{x} well other 9. WELL NO.

2. NAME OF OPERATOR Mountain Fuel Supply Company

3. ADDRESS OF OPERATOR

P. O. Box 1129, Rock Springs, Wyoming 82901

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: 890' FNL, AT TOP PROD. INTERVAL: 790' FEL AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE MATURE OF NOTICE, REPORT, OR OTHER DATA

10. FIELD OR WILDCAT NAME

7. UNIT AGREEMENT NAME

Wildcat 11. SEC., T., R., M., OR BLK. AND SURVEY OR

Fruitland L

28-30N-14W., NMPM

12. COUNTY OR PARISH 13. STATE New Mexico San Juan

14. API NO.

5. LEASE

15. ELEVATIONS (SHOW DF, KDB, AND WD)

SUBSEQUENT REPORT-OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE (NOTE: Report results of multiple completion or zone REPAIR WELL change on Form 9-330.) U. 9. 10. 19. 19. 19. 20. 20. 10. 10. PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* X (other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 12,448', PBD 0'.

Drilled out cement to 360', perforated with 4 holes at 320', set a cement retainer at 240', squeezed 200 sacks cement with 2% calcium 5 chloride into perforations at 320', no bubbling, set 15 sacks cement plug from 50' to surface, installed a dry hole marker.

Final report.

18. I hereby certify that the foregoing is true and correct

TITLE Drlg Supt.

(This space for Federal or State office use)

DATE

June 22, 1982

APPROVED AS AMENDED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore Liability under bond is retained until surface restoration is completed.

Subsurface Safety Valve: Manu. and Type ___

astructions on Reverse Side

FARMINGTON COPY