

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
JUN 30 1993

OIL CON. DIV.
DIST. 3

93 JUN 25 PM 2:46

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1090'FNL, 1850'FWL Sec.1, T-30-N, R-14-W, NMPM

5. Lease Number
NM-28760
6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Little Federal #2

9. API Well No.
30-045-

10. Field and Pool
Basin Dakota

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

06-22-93 MOL&RU. Blew down. Pump 20 BW down tbg. ND WH. NU BOP. TOOH w/tbg & pkr. Set cmt ret @ 6252'. PT tbg 1400#. Cmt plug 6435-6252' w/20 sx Class "B" cmt under ret, 5 sx on top. Pull up 20 stds. SDFN.

06-23-93 TIH, tag cmt @ 5452'. Approval f/BLM to change procedure received. Circ hole w/70 BW. PT csg 425#/5 min, ok. Perf 4 holes @ 5450'. Try to est rate, not taking water. Approval f/BLM to change procedure received f/R. Snow. TIH to 5448'. Cmt plug #2 w/35 sx Cl "B" cmt 5448-4990'. Pull up to 4834'. Try to squeeze cmt through perfs by press to 800 psi. Spot 24 bbl 9# 50 vis mud 4834-3300'. Perf 4 holes @ 3326'. Cmt plug #3 w/55 sx Cl "B" cmt 3326-2600'. Pull up to 2033'. Load hole, squeezed w/35 sx cmt outside csg @ 3300' w/1000 psi. Left 20 sx inside csg @ 3036'.

06-24-93 Tag cmt @ 3141'. Pull up to 3110'. Load hole w/40 bbl 9# mud. TOOH to 1694'. Cmt plug #4 1700-883' w/62 sx Class "B" cmt. TOOH to 862'. Reverse circ clean w/13 BW. Perf 2 holes @ 835' and 367' each. Set cmt ret @ 770'. Est rate. Cmt plug #5 835-560' w/104 sx Class "B" under ret, and 21 sx on top. TOC @ 493'. TOOH. Est rate out bradenhead. Cmt plug #6 367'-surface w/108 sx Cl "B" cmt, circ 2 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install dry hole marker. Released rig. Well plugged & abandoned.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 6/24/93

(This space for Federal or State Office use)
APPROVED BY [Signature] Approved as to plugging of the well bore.
Liability under bond is retained until

CONDITION OF APPROVAL, if any: surface restoration is completed.

APPROVED

Date 6/28/1993

DISTRICT MANAGER

NMOCD