

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator AMOCO PRODUCTION COMPANY		8. Farm or Lease Name Heath Gas Com "B"	
3. Address of Operator 501 Airport Drive, Farmington, New Mexico 87401		9. Well No. 1A	
4. Location of Well UNIT LETTER F 1490 FEET FROM THE North LINE AND 1450 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 29N RANGE 9W NMPM.		10. Field and Pool, or Wildcat Blanco Mesaverde	
15. Elevation (Show whether DF, RT, GR, etc.) 5713' GL		12. County San Juan	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Perf & Frac

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-15-77 Pressure tested casing to 3000 psi OK and spotted 500 gallons 15% HCl. Perforated 4274-78, 4284-93, 4334, 4371, 4386-92, 4420-26, 4482, 4506-18, 4526-42, 4546-50, 4555-77, 4584-92, 4607-12 and 4682-86 with 1 SPF. Fraced with 110,000 pounds sand in 60,500 gallons frac fluid. Dropped 69 balls in 3 stages. No breakdown pressure. AIR 100 BPM. Set bridge plug at 4250' and tested to 3000 psi OK. Perforated 3848, 3890-97, 3904-60, 3981-93, 4002-50, 4061, 4069, 4121, 4131, 4169-75, 4201-06 and 4223 with 1 SPF. Fraced with 155,000 pounds sand and 85,250 gallons frac fluid. Dropped 98 balls in 3 stages. No breakdown pressure. AIR 100 BPM. Landed 2-3/8" J-55 tubing at 4675'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED El Sobada TITLE Area Adm. Supvr. DATE 3-3-77

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: