

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1840' FNL, 900' FWL, Sec. 7, T-31-N, R-9-W, NMPM

5. Lease Number
SF-078439

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Johnston Federal #7A

9. API Well No.
30-045-22370

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

9-22-97 MIRU. ND WH. NU BOP. TOOH w/2 3/8" tbg. TIH w/4 1/2" gauge ring to 5000'.
TOOH. TIH w/4 1/2" CIBP, set @ 4950'. SDON.

9-23-97 TIH, tag top of CIBP @ 4950'. Load hole w/wtr. Load hole w/140 bbl wtr.
PT csg to 500 psi, failed. Plug #1: pump 27 sx Class "B" neat cmt @
4622-4950'. TOOH. TIH w/7" gauge ring to top of 4 1/2" lnr @ 3349'. TOOH.
TIH, perf 3 sqz holes @ 3560'. TOOH. TIH w/cmt retainer, set @ 3290'.
Load hole w/wtr. PT csg above cmt retainer to 500 psi, OK. Establish
injection. Plug #2: pump 53 sx Class "B" neat cmt below cmt retainer
outside 7" csg @ 3490-3560'. Pump 19 sx Class "B" neat cmt inside csg
above cmt retainer. TOOH to 3028'. Plug #3: pump 29 sx Class "B" neat
cmt inside csg @ 2875-3028'. TOOH to 2163'. Plug #4: pump 45 sx Class
"B" neat cmt inside csg @ 1929-2163'. TOOH to 621'. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed *Regina D. Spence* Title Regulatory Administrator Date 10/13/97

(This space for Federal or State Office use)

APPROVED BY JS/ Duane W. Spencer Title _____

Date OCT 23 1997

CONDITION OF APPROVAL, if any:

9-24-97 Plug #5: pump 31 sx Class "B" neat cmt inside csg @ 464-621'. TOOH. TIH, perf 3 sqz holes @ 360'. Establish circ down csg & out bradenhead. Plug #6: pump 161 sx Class "B" neat cmt down 7" csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill 7" csg & annulus w/5 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. (Joe Sanchez, BLM on location for plugging). Well plugged and abandoned 9-24-97.