## UNITED STATES DEPARTMENT OF THE INTERIOR

5.	LEASE
	NM-28760

6.	IF.	INDIA	١N.	ΑI	LOT	ΓEΕ	OR	TRI	BE	NA	ME

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas r	Little Federal
well well other	9. WELL NO.
2. NAME OF OPERATOR	4
ODESSA NATURAL CORPORATION ATTN: J. Strojek	Undesignated Pictured Cliffs
3. ADDRESS OF OPERATOR P.O. Box 3908, Odessa, Texas 79760	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
helow )	Section 1-T30N-R14W
AT SURFACE: 1115 FNL, 1/10 FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan New Mexico
AT TOTAL DEPTH: Same	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5881'F7, 5892'KB
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3001 1 7 3072 10
EST WATER SHUT-OFF	
RACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON* & AM U	
SEE ATTACHED	APR 3 1980
Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct FOR: ODESSA NATURAL CORP. Walsh Engr, SIGNED TITLE Corp.  Dewayne Blancett, Production Foreman (This space for Federal or State of	& Prod. 3/19/80
APPROVED BY TITLE	DATE
conditions of approval, if any:	cc' APPROVED
<b>,</b>	MAD 3 () 1980

\*See Instructions on Reverse Side

DISTRICT OIL & GAS SUPERVISOR

## ODESSA NATURAL CORPORATION

## LITTLE FEDERAL NO. 4

8-5/8", 28 lb. set at 99', 12-1/4" hole, cement circulated to surface.

4-1/2", 10.50 lb., set at 1867', 7-7/8" hole, cement circulated to surface.

Perforations: 1364'-1384'; 1420'-1434'; 1590'-1610'

Perforations: 1648'-1664' squeezed with 35 sacks 5/21/77.

Cement Retainer set at 1628'.

Formation Tops: Ojo Alamo 610'; Kirtland 785'; Fruitland 1210';

Pictured Cliffs 1650'

This well will be plugged in the following manner.

- 1. Spot and squeeze 45 sack plug 1620' to 1150'
- 2. Spot 25 sack plug across Ojo Alamo 840' to 560'
- 3. Spot 10 sack surface plug and set surface marker
- 4. Remove surface equipment
- 5. Clean up location and reseed to BLM specifications

