

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☒ other

2. NAME OF OPERATOR
ODESSA NATURAL CORPORATION Attn: J. Stroger

3. ADDRESS OF OPERATOR
P.O. Box 3908 Odessa, Texas 79760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1250' FSL, 790' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM-28760

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Little Federal

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Undesignated Fruitland

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 12-T30N-R14W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

30-045-22379

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5961' DF, 5962' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SEE ATTACHED

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct
FOR: ODESSA NATURAL CORPORATION

SIGNED

TITLE Walsh Engr. & Prod. DATE 3/19/80

Dewayne Blancett, Production Foreman

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ok 3/22

WALSH

APPROVED

*See Instructions on Reverse Side

MAR 30 1980
James F. Sims
JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR

ODESSA NATURAL CORPORATION

LITTLE FEDERAL NO. 6

8-5/8", 28.0 lbs. set at 86', 12-1/4" hole, cement circulated to surface.

4-1/2", 10 50 lbs., set at 1861', 7-7/8" hole, cement circulated to surface.

Perforations: 1254'-1262'; 1270'-1278'; 1295'-1304'; 1314'-1 26'

Formation Tops: Ojo Alamo 710'; Kirtland 910'; Fruitland 1200';
Pictured Cliffs 1708'

This well will be plugged in the following manner:

1. Spot 8 sack plug 1750' to 1650'
2. Spot and squeeze 35 sack plug across perforations 1620' to 1150'
3. Spot 25 sack plug 950' to 650'
4. Spot 10 sack surface plug and set surface marker
5. Remove surface equipment
6. Clean up location and reseed to BLM Specifications

