Form 9-331 (May 1963)

1190'N, 790'W

## UNITED STATES NT OF THE INTERIOR (Other instructions on re-

SUBMIT IN TRIPLICATE\*

Form approved. Budget Bureau No. 42-R1424.

SURVEY OR AREA

Sec. 18, T-30-N, R-9-W

GEOLOGICAL SURVEY	SF 078128
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reser Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.	7. UNIT AGREEMENT NAME
OIL GAS X OTHER	
2. NAME OF OPERATOR	8, FARM OR LEASE NAME
EL PASO NATURAL GAS CO.	DELHI TURNER
3. ADDRESS OF OPERATOR	9. WELL NO.
BOX 990, FARMINGTON, NEW MEXICO 87401	1A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
	BLANCO MESA VERDE
	11 SEC E P M OP DIE AND

NMPM 12. COUNTY OR PARISH | 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 6282' GL San Juan <u>New Mexico</u> 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: REPAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT-OFF Х

ALTERING CASING FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT SHOOT OR ACIDIZE ABANDON\* SHOOTING OR ACIDIZING ABANDONMENT\* CHANGE PLANS (Other) REPAIR WELL (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \* proposed work. I nent to this work.)
  - T.D. 3381'. Ran 83 joints 7", 20#, K-55 intermediate casing, 3368' set at 3381'. Cemented with 270 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1700'.
  - 11/27/77: T.D. 5651'. Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2423' set 3228-5651'. Float collar set at 5633'. Cemented with 429 cu. ft. cement. 18 hours.
  - 1/31/78: PBTD 5633'. Tested casing to 3500#, OK. Perfed C.H. 4550-60,4583-89,4614-36,4655-60,4710-19,4732-52,4778-98' w/18 SPZ. Fraced w/92,000# 20/40 sand and 100,400 gallons water. Dropped 6 sets of 18 balls each. Flushed w/6340 gallons water. Perfed Men. 4900-14,4914-28,4945-61,4978-88,5048-58, 5078-96' w/16 SPZ. Fraced w/62,000# 20/40 sand and 70,360 gallons water. Dropped 5 sets of 16 balls each. Flushed with 6800 gal. water. Perfed Massive P.L. 5163-75,5219-43,5258-76,5288-5300,5312-32,5344-54,5364-70' w/18 SPZ. Fraced with 90,110# 20/40 sand and 96,910 gallons water. Dropped 6 sets of 18 balls each. Flushed w/9450 gal. water. Perfed Lower P.L. 5421-31,5441-56, 5467-73,5495-5508,5533-41,5560-79' w/16 SPZ. Fraced w/56,000# 20/40 sand and 65,940 gallons water. Dropped 5 sets of 16 balls each. Flushed w/ 6590 gal. water.

18. I hereby certify that the foregoing is true and correct					
SIGNED J. J. L.	TITLE _	Drilling Clerk	DATE _	1/31/78	
(This space for Federal or State office use)			199		
APPROVED BY	TITLE _		DATE _	RECE	V <u>e</u> L
CONDITIONS OF APPROVAL, IF ANY:				FEB13	1978