

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other Instructions on reverse side)Form approved,
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SE 080597

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

GARTNER

9. WELL NO.

4A (PM)

10. FIELD AND POOL, OR WILDCAT

Blanco P.C. Ext.

Blanco M.V.

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35, T-30-N, R-8-W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1450'S, 800'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6365' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

08/09/77 T.D. 3541'. Ran 87 joints 7", 20#, K-55 intermediate casing, 3529' set at 3541'. Cemented with 395 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 1800'.

08/13/77 T.D. 5743'. Ran 56 joints 4 1/2", 10.5#, K-55 casing liner, 2562' set 3381-5743'. Float collar set at 5725'. Cemented with 425 cu. ft. cement. WOC. 18 hours.

10/07/77 P.B.T.D. 5725'. Tested casing to 3500#, OK. Perfed P.C. 3114-36, 3142-56, 3162-66, 3172-76' w/16 SPZ. Fraced with 40,000# 20/40 sand and 40,980 gallons water. Dropped 3 sets of 16 balls each. Flushed with 5290 gallons water. Perfed C.H. Men. 4705-10, 4740-45, 4763-75, 4819-28, 4844-74, 4889-95, 4921-29, 5044-56, 5067-74, 5106-11' w/16 SPZ. Fraced with 80,000# 20/40 sand and 80,000 gallons water. Dropped 8 sets of 16 balls each. Flushed with 6800 gal. water. Perfed upper P.L. 5189-97, 5262-87, 5324-51, 5361-65, 5386-5402, 5410-16, 5446-52' w/ 18 SPZ. Fraced with 92,000# 20/40 sand and 92,050 gallons water. Dropped 2 sets of 18 balls each. Flushed with 7000 gal. water. Perfed Lower P.L. 5508-20, 5552-64, 5577-86, 5620-28, 5638-54, 5692-98' w/14 SPZ. Fraced w/48,640# 20/40 sand and 50,800 gallons water. Dropped 4 sets of 14 balls each. Flushed w/5840 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. J. Buzco

TITLE

Drilling Clerk

DATE

10/15/77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

OCT 11 1977

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY