UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135 Expires: March 31, 1993

SUNDRY NOTICES AND REPO	DRTS ON WELLS	esignation and Serial No.
Do not use this form for proposals to drill or to deepen		NMSF - 078387 - A
Use "APPLICATION FOR PERMIT." 1	or such proposals fill	
	MAY 1 3 1999 17 II Deit	or CA, Agreement Designation
	OIL COM DA	,
1. Type of Well Oil Well Well Other	DIST. 3 B. WOI NO	me and No.
2. Name of Operator	Attention:	KERNAGHAN B 3A
AMOCO PRODUCTION COMPANY	MARY CORLEY 9. API W	all No.
3. Address and Telephone No.	281-366-4491 III Field	30-045-22421
P.O. BOX3092 HOUSTON, TX 77253	28 I-300-449 I 10. Field	and Pool, or Exploratory Area BLANCO MESAVERDE
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)	11. Coun	y or Parish, State
980 FSL 1480 FEL Sec. 29		•
		SAN JUAN NEW MEXICO
CHECK APPROPRIATE BOX(s) TO IN	DICATE NATURE OF NOTICE, REPORT,	OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
	M	_
Notice of Intent	Abandonment Change of Recompletion New Const	
	Plugging Back Non-Routin	e Fracturing
Subsequent Report	Casing Repair Water Shu Altering Casing Conversion	t-Off to Injection
Final Abandonment Notice	Other Dispose W	•
	(Note: Report results of mult	iple completion on Well Completion or Recompletion Report and Log form.
12 County Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in		iple completion on Well Completion or Recompletion Report and Log form. subsurface locations and measured and true vertical depths for all
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in markers and zones pertinent to this work.)*		
π arkers and zones pertinent to this work.)*	scluding estimated date of starting any proposed work . If well is directionally drilled, give	subsurface locations and measured and true vertical depths for all
rankers and zones pertinent to this work.)* 2/12/99 MIRUSU NDWH, NUBOP, TOH W/2 3/	ncluding estimated date of starting any proposed work . If well is directionally drilled, give	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/10/14/15/15/15/15/15/15/15/15/15/15/15/15/15/	B" TBG. TIH W/TBG & CIBP, set @ 5075'. Test () le to circ. to surface. Shot 2 holes @ 300' & circ t	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG &
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/10/14/15/15/15/15/15/15/15/15/15/15/15/15/15/	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/ TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3// TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3/TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 30 782' - 532'. 6th plug - 300' to surface & circ 2 Blowellhead & weld on P&A marker. In turned over to environmental group for surface response of the surface of the surfac	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3// TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3// TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 30 782' - 532'. 6th plug - 300' to surface & circ 2 Blowellhead & weld on P&A marker. In turned over to environmental group for surface response of the surface of the surfac	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3// TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 3 2 782' - 532'. 6th plug - 300' to surface & circ 2 Blowellhead & weld on P&A marker. In turned over to environmental group for surface results over the environmental group for surface results.	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.
2/12/99 MIRUSU NDWH. NUBOP. TOH W/2 3// TOH W/TBG. Run log & perf holes @ 750', unab spotted CMT plugs as follows: 1st plug - 200' @ 4th plug - 200' @ 2250' - 2050'. 5th plug - 250' @ used 312 SXS CLS B Neat, 15.6 PPG. Cut off 2/17/99 RDMOSU @ 10:00 hrs. Surface location	8" TBG. TIH W/TBG & CIBP, set @ 5075'. Test (le to circ. to surface. Shot 2 holes @ 300' & circ to 5075' - 4875'. 2nd plug - 200' @ 4250' - 4050'. 30 782' - 532'. 6th plug - 300' to surface & circ 2 Blowellhead & weld on P&A marker. In turned over to environmental group for surface response of the surface of the surfac	subsurface locations and measured and true vertical depths for all CSG to 500#. Held OK. o surface. TIH W/TBG & rd plug - 540' @ 3368' - 2827'. BLS up backside. Total CMT estoration.

itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficticious, or fraudulent statements or representations as to any matter within its jurisdiction.