Form 9-331 (May 1963)

APPROVED BY ...

CONDITIONS OF APPROVAL, IF ANY:

## UNITED STATES SUBMIT IN TRIPLICATES OTHER INTERIOR (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

GFOL	.OGICAL	. SURVEY

NM 012647

		Sals to drill or to deepen or parion FOR PERMIT—" for so	S ON WELLS they back to a different reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS		7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR				8. FARM OR LEASE NAME
El Paso Natural Gas Company				Riddle D
3. ADDRESS OF OPERATOR				9. WELL NO.
P O Box (	990 Farmino	ton New Mexico 8	37401	3A
P. O. Box 990, Farmington, New Mexico 87401 Location of well (Report location clearly and in accordance with any State requirements.				10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface  1015' S, 1685' E				Blanco Mesa Verde
				11. SEC., T., R., M., OR BLK. AND
101.	o, 1003			Sec. 22, T-31-N, R-9-W N.M.P.M.
14. PERMIT NO.		15. ELEVATIONS (Show wheth	ner DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
		6274' GL		San Juan New Mexic
16.	Check A	•	te Nature of Notice, Report, o	SEQUENT REPORT OF:
TEST WATER SH	UT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL
FRACTURE TREAT	e	MULTIPLE COMPLETE	FRACTURE TREATMENT	X ALTERING CASING
SHOOT OR ACIDI	ze	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL		CHANGE PLANS	(Other)	when A multiple completion on Well
(Other)			Completion or Reco	ults of multiple completion on Well ompletion Report and Log form.)
17. DESCRIBE PROPOS proposed work nent to this wo	c. If well is direct	ERATIONS (Clearly state all perionally drilled, give subsurface	tinent details, and give pertinent da locations and measured and true ver	tes, including estimated date of starting any rtical depths for all markers and zones perti-
05-09-77 05-12-77	at 3406'. minutes. T.D. 5753'.	Cemented with 357 Top of cement at 1 Ran 78 joints 4 Float collar se	700'. 1/2", 10.5#, K-55 cas	C. 12 hours, held 1200#/30
05-18-77	5075-92, 51 Fraced with sets. Flus 5346-58, 53 122,700#3 each. Flus 5605, 5628- 20/40 sar	.80-90' with 12 shows a 65,000#20/40 standard with 6700 gal 588-5402, 5442-50, 20/40 sand and 95, shed with 15,510 gal 38, 5649-55, 5682	and and 58,250 gallons lons water. Perfed 52 5466-72' with 12 shot 240 gallons water. Drallons water. Perfed 90' with 10 shots perons water. Propped 5	water. Dropped no ball 38-52, 5279-99, 5330-36, s per zone. Fraced with opped 9 sets of 12 balls 5546-50, 5575-81, 5593-zone. Fraced with 35,000# sets of 10 balls each.
18. I hereby certify	·		Drilling Clerk	MAY 20 1977
SIGNED A	Federal or State o	CO TITLE	DIMMIS CLEIK	
APPROVED BY		TITLE		U. S. GEOLOGICAL SURVEY DATE
MILLIOTED DI				

TITLE \_