

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1035'S, 875'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON* ☐ YES ☒ NO ☐ BOTH OF INTEREST

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/26/77: TD 3348'. Ran 81 jts. 7", 20#, K-55 intermediate casing, 3337' set at 3348'. Cemented with 914 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 1200'.

10/31/77: TD 5550'. Ran 87 jts. 4 1/2", 10.5#, K-55 casing liner
2785' set 2765-5550'. Float collar set at 5534'. Cemented
with 320 cu. ft. cement. WOC 18 hours.

3/20/78: PBTD 5534'. Tested casing to 3500#, OK. Perfed Lower P.L. 5294-5301, 5312-22, 5358-69, 5390-95, 5405-08, 5430-36, 5512-20' w/10 SPZ. Fraced with 40,000# 20/40 sand and 45,750 gallons

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft. (OVER)

18. I hereby certify that the foregoing is true and correct

SIGNED N. G. Bruce TITLE Drilling Clerk DATE 3/23/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

CONDITIONS OF APPROVAL, IF ANY:

***See Instructions on Reverse Side**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Dropped 6 sets of 10 balls each. Flushed w/6500 gallons water. Perforated Massive P.L. 5024-38, 5053-66, 5080-93, 5104-22, 5122-40, 5140-58, 5172-91, 5208-33' w/18 SPZ. Fraced w/138,000# 20/40 sand and 145,500 gallons water. Dropped 7 sets of 18 balls each. Flushed with 7000 gal. water. Perforated Menefee 4738-46, 4756-74, 4784-98, 4813-20, 4837-59, 4885-97, 4928-38, 4928-38, 4948-54, 4972-82, 4995-5006' w/18 SPZ. Fraced w/100,000# 20/40 sand and 100,000 gallons water. Dropped 9 sets of 18 balls each. Flushed with 6500 gal. water. Perforated Cliff House 4404-12, 4494-98, 4516-20, 4530-36, 4611-30, 4630-50, 4672-94' w/16 SPZ. Fractured w/74,000# 20/40 sand and 74,000 gallons of water. Dropped 6 sets of 16 balls each. Flushed w/6000 gallons of water.