Emm 9 331 (May 1963)

REPAIR WELL

(Other)

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on verse side)

CHANGE PLANS

SUBMIT IN TRIPLACATES

Form approved, Budget Bureau No. 42 R1421. 5. LEASE DESIGNATION AND SERIAL NO.

SF 080597 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plun, back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals,) 7. UNIT AGREEMENT NAME OIL OTHER NAME OF OPERATOR S. FARM OR LEASE NAME EL PASO NATURAL GAS COMPANY GARTNER ADDRESS OF OPERATOR 9. WELL NO. BOX 990, FARMINGTON, NEW MEXICO 87401 6A LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)

At surface 10. FIELD AND POOL, OR WILDCAT BLANCO MESA VERDE 1630'S, 1780'E 11. SEC., T., R., M., OR BLK. AND Sec. 27, 1 - 30 - N, R-8-W N.M.P.M. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 12. COUNTY OR PARISH 13. STATE 6240' GL San Juan New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: XTEST WATER SHUT-OFF PULL OR ALTER CASING REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE PRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON\* SHOOTING OR ACIDIZING ABANDONMENT\*

- (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
  - T.D. 3419'. Ran 84 joints 7", 20#, K-55 intermediate casing, 3407' set 8/26/77 at 3419'. Cemented with 354 cu.ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 1900'.
  - T.D. 5718'. Ran 75 joints 4 1/2", 10.5#, K-55 casing liner, 2470' set 8/30/77 3248-5718'. Float collar set at 5699'. Cemented with 431 cu.ft. cement. W.O.C. 18 hrs.
  - 9/27/77P.B.T.D. 5699'. Tested casing to 3500#, O.K. Perfed C.H. - Men. 4583, 4672, 4811, 4829, 4842, 4889, 4895, 4939, 4946, 5034, 5040, 5122, 5144, 5152, 5160  $w/1 \ SPZ$ . Fraced with 56,000# 20/40 sand and 116,200 gallons water. Flushed with 6400 gallons water. Perfed P.L. 5255, 5261, 5285, 5290, 5295, 5300, 5317, 5335, 5348, 5369, 5380, 5387, 5412, 5437, 5474, 5494, 5501, 5521, 5549, 5619, 5637' w/l SPZ. Fraced with 67, 000 # 20/40 sand and 125,600 gallons water. Flushed with 6900 gal. water.

OIL CON. COM. 18. I hereby certify that the foregoing is true and correct DIST. 3 Drilling Clerk SIGNED A (This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

1111