

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.

SF 080597

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gartner

9. WELL NO.

2A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T-30-N, R-8-W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR
EL PASO NATURAL GAS COMPANY

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1720'S, 1530'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6150' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/14/77 T.D. 3256'. Ran 78 joints 7", 20#, K-55 intermediate casing, 3245' set at 3256'. Cemented with 332 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 2800'.

9/17/77 T.D. 5537'. Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2456' set 3081-5537'. Float collar set at 5520'. Cemented with 425 cu. ft. cement. WOC 18 hours.

10/12/77 P.B.T.D. 5520'. Tested casing to 3500#, OK. Perfed C.H. Men. 4437, 4565, 4648, 4654, 4667, 4672, 4677, 4687, 4694, 4705, 4796, 4821, 4830, 4853, 4870, 4934, 4962, 4979, 5007, 5013, 5019' w/1 SPZ. Fraced with 75,000# 20/40 sand and 72,870 gallons water. Flushed with 6090 gallons water.. Perfed P.L. 5096, 5102, 5108, 5114, 5133, 5140, 5147, 5154, 5161, 5177, 5197, 5222, 5230, 5245, 5278, 5306, 5339, 5356, 5365, 5385, 5412, 5475, 5499' w/1 SPZ. Fraced with 90,000# 20/40 sand and 92,106 gallons water. Flushed with 6552 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED *A. H. Diers*

TITLE Drilling Chief

DATE 10/13/77

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE RECEIVED

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY

OCT 14 1977