Fort (-331 (May 1963)

UNITED STATES

SUBMIT IN TRIPLICATE*
(Other instructions on re-

Form approved. Budget Bureau No. 42-B1424.

SUNDRY NOTIC (Do not use this form for proposal Use "APPLICATION. (III GAS	EOLOGICAL SURVEY CES AND REPORTS is to drill or to deepen or plug TON FOR PERMIT—" for such a	ON WELLS back to a different reservoir.	SF 080597 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this form for proposals Use "APPLICAT"	CES AND REPORTS is to drill or to deepen or plug TON FOR PERMIT—" for such i	ON WELLS back to a different reservoir.	
OIL CAS C		proposals.)	
OIL GAS [7]			7. UNIT AGREEMENT NAME
WELL WELL X OTHER			
NAME OF OPERATOR			8. FARM OR LEASE NAME
EL PASO NATURAL GAS CO.			GARTNER 9. WELL NO.
BOX 990, FARMINGTON, NEW MEXICO 87401			1A
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)			10. FIELD AND POOL, OR WILDCAT
At surface			BLANCO MESA VERDE
1170'N, 1840'W			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
			Sec. 28, T-30-N, R-8-W
4. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			NMPM 12. COUNTY OR PARISH 13. STATE
14. PERSII AU.	,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	San Juan New Mexico
	6191' GL	11 1 1 1 B	
16. Check App	propriate Box To Indicate	Nature of Notice, Report, or	Other Data
NOTICE OF INTENTION TO:			EQUENT REPORT OF:
TEST WATER SHUT-OFF PU	CLL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL
FRACTURE TREAT MU	ULTIPLE COMPLETE	FRACTURE TREATMENT	X ALTERING CASING
SHOOT OR ACIDIZE AB	BANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
	HANGE PLANS	(Other)(Note: Report_resu	lits of multiple completion on Well
(Other)	ATIONS (Clearly state all pertine	out details and give pertinent dat	mpletion Report and Log form.) tes, including estimated date of starting any
proposed work. If well is directions nent to this work.)*	ally drilled, give subsurface loc	sations and measured and true ver	tical depths for an markers and zones perti-
3296'. Ce		i.ft. cement. WOC 12	ate casing, 3285' set at hours, held 1200#/30
	'. Float collar se		casing liner, 2436' set ed with 425 cu. ft. cement.
4689, 4694 1 SPZ. Fr with 6426 5072, 5080 5199, 5214 80,000# 20 Perfed Low w/16 SPZ.	4, 4699, 4704, 4709 raced with 50,000# gallons water. Pe 0, 5134, 5138, 5142 4, 5219, 5235, 5259 0/40 sand and 82,11 ver P.L. 5364-73, 5 Fraced with 50,00	20, 4726, 4744, 4815, 20/40 sand and 52,12 erfed Upper P.L. 5005, 5146, 5163, 5167, 5266, 5275, 5295, 0 gallons water. F1	
	true and correct		

*See Instructions on Reverse Side

1977 NOV 4

a GEOLOGICAT COL