Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF - 078198
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Nye 9. WELL NO.
2. NAME OF OPERATOR	#3A
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesaverde/Basin Dakota
P.O. Drawer 570, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	Section 1, T30N, R11W
AT SURFACE: 800' FSL & 800' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
market 1 st	15 ELIVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FEACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL SUBSEQUENT REPORT OF: SUBSEQUENT REPORT	, 1982
FRACTURE TREAT SHOOT OR ACIDIZE T T T T T T T T T T T T T	4 10°
REPAIR WELL	(NOTES report results of multiple completion or and
PULL OR ALTER CASING [OCICA Nichange on Form 9–330.)
MULTIPLE COMPLETE	(NOTES Report results of multiple completion or zone OCICA Ni change on Form 9–330.)
ABANDON*	
(other)	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent 	rectionally drilled give subsurface locations and
ll-ll-82 Pulled out of hole with 1-1/2" & 2-3	/8" tubing strings.
II-I2-82 Laid down 5 bad joints 2-3/8" tubing	. Redressed packer.
11-16-82 Tripped in hole with 2-3/8" and pa	cker sat at 5441.31'. Hydrotested
ali tubing above nacker langed 2-3	/8" tubing at 7025 ! packon cat
at 5441'. Tripped in hole with 1-1/out plugs.	2" tubing landed at 4784'. Pumped
out prugs.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Engineer	DATE December 13, 1982
COCEPTED TOP RECURS Poace for Federal or State office	
CONDITIONS OF APPROVAL, IF ANY:	DATE
DEC <u>1</u> m 1982	

*See Instructions on Reverse Side