

Submit 3 Copies 3 NMOCD
to Appropriate 1 File
District Office
1 Conoco

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-103
Revised 1-1-89

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO.
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Dugan Production Corp.		6. State Oil & Gas Lease No. V-81
3. Address of Operator P.O. Box 420, Farmington, NM 87499		7. Lease Name or Unit Agreement Name State 36
4. Well Location Unit Letter B : 870 Feet From The North Line and 1700 Feet From The East Line Section 36 Township 30N Range 14W NMPM San Juan County		8. Well No. 2
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5487' GL		9. Pool name or Wildcat Basin Dakota

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plug by spotting Class B + 6% gel. plugs as follows:

1. 100' plug across Dakota top @ 5773.
2. 100' plug across Gallup top @ 5184.
3. Perforate 50' below Mesa Verde top @ 2700' and spot 100' plug inside and outside 4½" casing.
4. Perforate 50' below Pictured Cliffs top @ 1195 and spot 335' plug to cover Fruitland top @ 860'.
5. Perforate 50' below surface casing @ 326' and circulate cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John Alexander TITLE Operations Manager DATE 6/30/92
TYPE OR PRINT NAME John Alexander TELEPHONE NO.

(This space for State Use)

Original Signed by CHARLES GHOLSON TITLE DATE JUN 30 1992
APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY: