

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

**SF 076337**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

**Heath Gas Com "C"**

9. WELL NO.

**1A**

10. FIELD AND POOL, OR WILDCAT

**Blanco Mesaverde**

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

**SE/4 SW/4 Section 31**

**T-30-N, R-9-W**

12. COUNTY OR PARISH

**San Juan**

13. STATE

**NM**

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

**AMOCO PRODUCTION COMPANY**

3. ADDRESS OF OPERATOR

**501 AIRPORT DRIVE, FARMINGTON, NM 87401**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface **1190' FSL x 850' FWL, Section 31, T-30-N, R-9-W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

**5756' GL**

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

**Spud & Set casing**


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**Spudded 13-3/4" hole 12/17/77. Drilled to 274'. Set 9-5/8" casing at 274' and cemented with 300 sx Class "B", 2% CaCl<sub>2</sub>, circulated 50 sx good cement. Tested to 500 psi for 30 minutes, held OK.**

**Drilled 8-3/4" hole to 2746'. Set 7" 20# casing at 2746', cemented with 460 sx Class "B", 50:50 Poz, 6% Gel, 2# Tuf Plug, followed by 100 sx Class "B", 2% CaCl<sub>2</sub>, circulated 15 sx good cement. Pressure tested to 1000 psi for 30 minutes, held OK.**

**Drilled 6-1/4" hole to a total depth of 4715'. Set 4-1/2", 10.5# casing liner at 2538-4715'. Cemented with 190 sx Class "B", 50:50 Poz, 2# Tuf Plug per sx, followed by 100 sx Class "B", 50:50 Poz, 6% Gel. Reversed out 10 bbls good cement.**



18. I hereby certify that the foregoing is true and correct

SIGNED

*E. E. Sabada*

TITLE

**Area Adm. Supervisor**

DATE

**1/31/78**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

**RECEIVED**

**FEB 1 1978**

\*See Instructions on Reverse Side

U.S. Geological Survey  
Farmington, N.M.

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.