

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-045-22762

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No. _____

7. Lease Name or Unit Agreement Name
State Gas Com "J"

8. Well No. #1A

9. Pool name or Wildcat
Blanco Mesaverde

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER _____

2. Name of Operator
Amoco Production Company Attn: John Hampton

3. Address of Operator
P.O. Box 800, Denver, Colorado 80201

4. Well Location
Unit Letter F : 1450' Feet From The North Line and 1915' Feet From The West Line
Section 36 Township 30N Range 10W NMPM San Juan County _____

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
5656' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐ CASING TEST AND CEMENT JOB ☐

OTHER: Abandon cathodic protection well ☒ OTHER: _____ ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The cathodic protection well associated with the above well will be plugged and abandoned per the attached procedure.

RECEIVED
JUN 11 1990
OIL CON. DIV.
DIST. 3

Please contact Cindy Burton (303)830-5119 if you have any questions.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John Hampton TITLE Sr. Staff Admin. Supr. DATE 6/8/90

TYPE OR PRINT NAME John Hampton

(This space for State Use)

TELEPHONE NO. 303-830-5025

Original Signed by **FRANK T. CHAVEZ**

APPROVED BY _____ TITLE MANAGER DISTRICT 3 DATE JUN 12 1990

CONDITIONS OF APPROVAL, IF ANY: _____

GROUND BED ABANDONMENT

WELL NAME: STATE J-1A

LOCATION: S36-T30-R9

- 1) Weld 6 " dia. spool with diverter line to pit
- 2) MIRU
- 3) Wash in hole with 1 1/4" work string. Circulate out coke breeze. Pull anodes as they come free. Wash hole to 290 ft.
- 4) Pump 90 sx of neat cement w/ 1/4 lb. sk. Flocele. Pull out work string.
- 5) Top off hole with cement, set flexible pipeline marker as PxA marker.
- 6) RDMO

Ground Bed Specifications

TD 290 ft.

Hole Dia. 6³/₄ inches.

Casing Dia. 6³/₄ inches

Casing Length 43 ft.

JAB.GRA

DATA SHEET NO. 1-7-2

COMPANY Amccc JOB No 10265 DATE 8-14-80
WELL State "J" #1A PIPELINE _____
LOCATION: SEC. 36 TWP. 30N RGE. 9W CO. _____ STATE N.M.
ELEV. _____ FT: ROTARY _____ FT: CABLE TOOL _____ FT: CASING 40 FT.
GROUNDBED: DEPTH 280 FT. DIA. _____ IN. GAB _____ LBS. ANODES 6

DEPTH, FT.	DRILLER'S LOG	DRILL PIPE TO STRUCTURE			EXPLORING ANODE TO STRUCTURE			DEPTH, TOP OF ANODES
		E	I	R	E	I	R	
50								
55							2.6	
60							2.5	
65							2.9	
70							2.5	
75							2.9	
80							4.1	
85							4.3	
90							4.1	
95							3.8	
100							2.6	
105							2.3	
110							2.5	
115							2.3	
120							2.4	
125							2.1	
130							2.2	
135							3.0	
140							4.0	
145							4.5	
150							3.3	
155							2.8	
160							2.9	
165							3.4	
170							3.8	
175							3.9	
180							3.5	
185				2.2			2.7	6
190							3.0	
195							3.0	
200				1.8			2.3	5
205							2.5	
210							2.8	
215							3.8	
220							4.4	
225							5.5	
230							5.5	
235							5.1	
240							3.6	
245				2.0			2.6	4
250							2.5	
255				1.9			2.6	3
260							2.7	
				2.8			3.9	2

GROUNDED RESISTANCE: (1) VOLTS _____ + AMPS _____ - _____ OHMS

(2) VIBROGROUND 0.04 OHMS

CATHODIC PROTECTION STATUS

IN-SERVICE REPORT

CPS# PINOCO Located at MP BLANCO Work Order # PHASE 5 10265
on the STATE JIA line

In Service Date 3-2-83 Watt-Hour Meter # 1026113

Power Vendor CITY Initial Reading 0000

POWER UNIT DATA

Manufacturer RIO

Model No. DR-2

Serial No. 800682

D.C. Capacity 28 Volts 12 Amperes

A.C. Rating 220 / 440 Volts 2/1 Amperes 1 Phase

Rectifier Set for 220 Volts

A.C. Input 240 Volts Amperes

D.C. Output 3.91 VOLTS JIA 6.42 Amperes

P/S Potentials at Negative JIA 0.82 0.97 -Volts

WELL NO. 1 NATIVE RECT. ON
-Volts

GROUND BED DATA

No. of Anodes 60 Type and Size DS1-D

Anode Lead Cable Data #8 OR-2

Coke Type GAB Amount of Coke 3800

Positive Cable: Size #8 Type OR-2

INSTALLATION DATA:

Hole Depth & Diameter 290' x 6 3/4"

Lineal Feet Casing 43'

Soil Strata Log Attached Yes ☒ No ☐

Remarks:

[Signature]