

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other _____

2. NAME OF OPERATOR
EL PASO NATURAL GAS COMPANY

3. ADDRESS OF OPERATOR
Box 990, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1710'N, 925'W
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	☐	☒
FRACTURE TREAT	☐	☒
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other)		

5. LEASE
SF 078438

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 32-9 Unit

8. FARM OR LEASE NAME
San Juan 32-9 Unit

9. WELL NO.
1 A

10. FIELD OR WILDCAT NAME
Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-31-N, R-9-W, N.M.P.M.


12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6637' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-2-78 T.D. 3867'. Ran 127 joints 7", 20#, K-55 intermediate casing, 3850' set at 3867'. Cemented with 491 cu. ft. cement. W.O.C. 12 hours, held 1200#/30 minutes. Top of cement at 3500'.

5-6-78 T.D. 6218'. Ran 77 joints 4 1/2", 10.5#, K-55 casing liner, 2495' set 3723-6218'. Float collar set at 6201'. Cemented with 431 cu. ft. cement. WOC 18 hours.

7-16-78 P.B.T.D. 6201'. Tested casing to 3500#, OK. Perfed C.H. 4995, 5246, 5291, 5309, 5317, 5323, 5339, 5343, 5354, 5361, 5368, 5444, 5478, 5566, 5573, 5580' w/1 SPZ. Fraced with 70,500# 20/40 sand and 142,212 gallons water. Flushed with 7560 gallons water. Perfed Lower & Mass. P.L. 5674, 5679, 5724, 5731, 5736, 5742, 5748, 5753, 5764, 5794, 5811, 5816, 5831, 5863, 5902, 5944, 5950, 5977, 5982, 5995, 6033, 6064 w/1 SPZ. Fraced with 76,000# 20/40 sand and 153,930 gallons water. Flushed (OVER) Subsurface Safety Valve: Manu. and type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED N. D. Basso TITLE Drilling Clerk DATE 8-10-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

With 7896 gal. water.