

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

SF 079082

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Northeast Blanco Unit Agrmt

No. 1, Sec. 929

8. FARM OR LEASE NAME

Northeast Blanco Unit

9. WELL NO.

66

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

F-30-31N-7W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Blackwood & Nichols Co., Ltd.

3. ADDRESS OF OPERATOR

P. O. Box 1237, Durango, Colorado 81301

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1990' F/NL - 490' F/WL

At top prod. interval reported below

Same

At total depth

Same

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 5-20-78 16. DATE T.D. REACHED 5-28-78 17. DATE COMPL. (Ready to prod.) 7-14-78 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6280' GL 19. ELEV. CASINGHEAD 6282'

20. TOTAL DEPTH, MD & TVD 5934' 21. PLUG, BACK T.D., MD & TVD 5886' 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 5934' ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* Cliffhouse 5120', Menefee 5194', Point Lookout 5475' 25. WAS DIRECTIONAL SURVEY MADE Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN Induction-Gamma Ray, FDC and SNP Logs 27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	36.00#	255'	12-1/4"	150 sacks circulated	
7"	23.00#	3510'	8-3/4"	300 sacks top cement 1400	

29. LINER RECORD 30. TUBING RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4-1/2"	3348'	5934'	300		2-3/8"	5860'	

31. PERFORATION RECORD (Interval, size and number)
5120' - 5444' - 56 holes
5490' - 5850' - 52 holes
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED
5120' - 5444' 77,000 gals water
66,000 lbs. #20-40 sand
5490' - 5850' 93,756 gals water
80,000 lbs. 20-40 sand

33.* PRODUCTION

DATE FIRST PRODUCTION Not connected PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Shut-in WELL STATUS (Producing or shut-in)

DATE OF TEST Not tested HOURS TESTED CHOKE SIZE PROD'N. FOR TEST PERIOD OIL—BBL. GAS—MCF. WATER—BBL. GAS-OIL RATIO

XXX TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE OIL—BBL. GAS—MCF. WATER—BBL. OIL GRAVITY-API (CORR.)

Shut-in 860PSI 860 PSI Estimated 2774 MCF

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) TEST PERIOD

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED DeLasso Loos TITLE District Manager DATE 7-21-78

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Animas	1130'	2080'			740'	1°
Ojo Alamo	2080'	2245'			1247'	3/4°
Kirtland	2245'	2930'			1562'	3/4°
Fruitland	2930'	3195'			2050'	3/4°
Pictured Cliffs	3195'	3430'			2564'	1°
Lewis	3430'	4800'			2632'	3/4°
Cliffhouse	4800'	5120'			3137'	1°
Massive Cliffhouse	5120'	5194'			3510'	1°
Menefee	5194'	5475'			4008'	1°
Point Lookout	5475'	5610'			5930'	1°
Mancos	5610'	--				