NO. OF COPIES RECEIVED	· .		Form C-103	
DISTRIBUT: ON	IBUT'ON		Supersedes Old	
SANTA FE	NEW MEXICO OIL CON	SERVATION COMMISSION	C-102 and C-103 Effective 1-1-65	
FILE	7			
U.S.G.S.	7	:	5a. Indicate Type of Lease	
LAND OFFICE	7		State X Fee	
OPERATOR 1 -	7		5. State Oil & Gas Lease No.	
	<b>-</b>		E-5382	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)				
OIL GAS XX	OTHER-		7. Unit Agreement Name Northeast Blanco Unit Agreement #1, Sec.929	
2. Name of Operator			8, Farm or Lease Name	
Blackwood & Nichols	Co., Ltd.		Northeast Blanco Unit	
3. Address of Operator			9. Well No.	
	ango, Colorado 81301		39A	
4. Location of Well			10. Field and Pool, or Wildcat	
UNIT LETTERD	1190' FEET FROM THE North	LINE AND 11901 FEET FROM	Blanco Mesaverde	
THE West LINE, SECT	10N 36 TOWNSHIP 31N	RANGE 8W NURM		
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County	
	6456' (	GL	San Juan	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	Marianing Casing	
TEMPORARILY ASANDON		COMMENCE DRILLING OPNS.	PLUE AND ASSING COM.	
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB X	MHIL COW.	
OTHER		OTHER	MAR COM. COM.	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1603.				
2-16-78 Moved on location and rigged up. Spudded 12-1/4" surface hole @ 2:00 PM.  Drill to 236' KB. Ran 6 Jts. (218') 9 5/8" 36# H-40 Csg. and set @ 232' KB - cemented with 175 sacks Class "B" with 2% CaCl and 1/4# Flocele/sack. Cement circulated, plug down @ 11:00 P.M W.O.C. 12 hrs.				
2-17-78 W.O.C. 12 hrs Test 9 5/8" Csg. to 800 PSI for 1/2 hr Held O.K.				
2-22-78 Drill 8 3/4" hole to 3645' - Ram 95 Jts. (3633') 7" 23# K-55 Cag. and net @ 3645' KB - cemented with 200 sacks Howco Lite with 1/4# Flocele/sack and 100 sacks Class "B" with 2% CaCl and 1/4# Flocele/sack - plug down @ 4:30 P.M ran temperature survey. Top cement 1500' - 2-23-78 test csg. @ 1000 PSI O.K.				
2-25-78 Gas drilled 6	5-78 Gas drilled 6 $1/4$ " hole to 6083' KB. Logs - Induction Gamma Ray, FDC and SNP.			
2-27-78 Ran 56 Jts. (2588') 4 1/2", 10.5# K-55, with Baker Oil Tools liner hanger and float equipment and set @ 6060' KB - float collar @ 6013' KB, top liner @ 3472' KB, cemented with 325 sacks 50-50 POZ with 2% gel, 6 1/2# fine Gilmonite/mk, 0.6% fluid loss additive and 1/4# Flocele/sack. Plug down @ 4:30 A.M set pack off and reversed out approximately 17 barrels cement. Waiting on completion.				

SUPERVISOR DIST. #3

3 1978

MAR MAR

CONDITIONS OF APPROVALLIF ANY