

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

SF 078439

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johnston-Federal

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde Field

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Section 7-T31N-R9W

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Union Texas Petroleum, A Division of Allied Chemical Corporation

3. ADDRESS OF OPERATOR

Suite 1010, 1860 Lincoln Street, Denver, Colorado 80295

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

SW SE (875' FSL, 1550' FEL) Section 7-T31N-R9W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6652 GR

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Our approved Application for Permit to Drill stated that we would cement 8-5/8" surface casing at 290 ft. and 5-1/2" production casing at T.D. (3600 ft.). In order to reduce drilling problems due to lost circulation, we wish to change our plans as follows:

1. Surface pipe - No change.
2. 5-1/2" OD 14#/ft. K-55 new casing to be cemented at approximately 3200 ft. with sufficient volume to circulate to surface.
3. Gas drill 4-3/4" hole to 3600 ft. (TD).
4. Cement 4" OD 11.6#/ft. flush joint liner from 3150 ft. to 3600 ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Oil Engineer

TITLE

Petroleum Engineer

DATE

August 22, 1978

(This space for Federal or State office use)

RECEIVED

APPROVED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

SEP 2 - 1978

DATE

DENVER

P. T. McGRATH

*See Instructions on Reverse Side

