

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1010'N, 990'W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-27-78: TD 3376'. Ran 81 jts. 7", 20#, KS intermediate casing, 3364' set at 3376'. Cemented w/434 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 2550'.

11-30-78: TD 5656'. Ran 78 jts. 4 1/2", 10.5#, KS casing liner, 2480' set 3176-5656'. Float collar set at 5640'. Cemented w/428 cu. ft. cement. WOC 18 hours.

4-02-79: PBTD 5640'. Tested casing to 3500#, OK. Perfed Mass. & Lower P.L. 5237, 5246, 5255, 5264, 5273, 5282, 5295, 5304, 5313, 5328, 5337, 5346, 5355, 5375, 5408, 5430, 5460, 5484, 5508, 5515, 5535, 5545, 5572, 5580' w/1 SPZ. Fraced w/98,000# 20/40 sand and 187,130 gal. water. Flushed w/6765 gal. water. Perfed C.H. & Men. 4579, 4595, 4609, 4616, 4623, 4643, 4653, 4663, 4710, 4717, 4724, 4731, 4740, 4794, 4804, 4912, 4928, 4935, 4979, 4989, 5023, 5035, 5071, 5103, 5114' w/1 SPZ. Fraced w/100,000# 20/40 sand and 200,000 gal. water. Flushed w/6325 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED N. G. Diaco TITLE Drilling Clerk DATE April 3, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Gymnoc

