Form 9-331 May 1963)

SHOOT OR ACIDIZE

REPAIR WELL

## UNITED STATES DEPARTMENT OF THE INTERIOR

ABANDON\*

CHANGE PLANS

SUBMIT IN TRIPLICATE\* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

Casing Report

GEOLOGICAL SURVEY			SF-077282
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WE'LL WELL OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			8. FARM OR LEASE NAME
Southland Royalty Company			Grenier "A"
3. ADDRESS OF OPERATOR			9. WELL NO.
P.O. Box 570, Farmington, NM 87401			#1-A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  1170' FNL & 1770' FWL			10. FIELD AND FOOL, OR WILDCAT Blanco Pictured Cliffs Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
			Section 26, T30N, R10W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6151' GR		San Juan NM
16. Check	Appropriate Box To Indicate N	ature of Notice, Report, or (	Other Data
NOTICE OF INTENTION TO: SUBSE			UENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING MULTIPLE COMPLETE	WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WELL ALTERING CASING

- (Other)

  (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

  17. Describe proposed or completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
  - 6-25-78 Ran 76 jts. of 7", 20#, K-55, ST & C csg. set @ 3034'. Cemented w/170 sxs 50/50 C. "B" poz w/6% gel & 1/4# flocele per sx followed by 70 sxs C1. "B" w/2% CaCl<sub>2</sub> & 1/4# flocele per sx. Plug down @ 9:20 AM, 6-25-78.
  - 6-28-78 Ran 56 jts. of 4 1/2",10.5#, K-55, ST & C csg. set from 2874' to 5336'. Cemented w/295 sxs 50/50 C1. "B" poz w/6% gel, 1/4# gel flake per sx & 6% D-60. Plug down @ 5:37 PM, 6-28-78.

