API#

30-045-23076

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator E	BURLIN	IGTON	RESOURC	ES OIL & GA	s co.		Lease	GRENIER A			Well No.	1A
Location									· · · · · · ·			
of Well:	Unit	С	Sect	26	Twp.	030N	Rge.	010W	County	SAN JUAN		
			NAME OF	RESERVOIR	•			YPE OF PROD.		OD OF PROD.	DD	OD. MEDIUM
								(Oil or Gas)		v or Art. Lift)	1	Tbg. or Csg.)
Upper Completion	FRUITLAND/PICTURED CLIFFS							Gas	Flow			Casing
Lower Completion	MESAVERDE						Gas	Flow			Tubing	
					PRE-I	FLOW SHUT-IN	N PRESS	URE DATA	<u> </u>		L	
Upper	Hour, date shut-in Length of time shut-in							ess. psig		Stabilized? (Ye	s or No	
Completion		4/17	/98	120 Hours			1	212		- (165 OF 140)		
Lower Completion	4/17/98		72 Hours			235						
	-				•	FLOW TE	ST NO.					
Commenced	at (hour	,date)*			4/20/98			Zone producing (Upper or I	ower) LO	NER	
TIME	LAPSED TIME		TIME	PRESSURE				PROD. ZONE		200	VER	
(hour,date)	SINCE*		Upper Completion Lower Comp		letion			REM	EMARKS			
4/21/98	96 Hours		214	214 115		-					*****	
4/22/98	120 Hours		216 107				RECEIVER			VED		
										JUL	1 1 9	1999
						_				@[[L @(D[XI	DODG.
											M. S	} • कि∏ A %
roduction rate	during t	est.		<u> </u>								
Dil:	BOPD based on			Bbls. in			Hours.	Hours. Grav.		GOR		
ias:				MCFPD; Testa	ed thru (O	rifice or Meter):						
								-				
					MID-T	EST SHUT-IN	PRESSU	RE DATA				
Upper Completion	Hour,	date shu	ıt-in	Length of time shut-in			SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in Length of time shut-in				SI press. psig Stabiliza			Stabilized? (Yes	1? (Yes or No)			

(Continue on reverse side)

hereby certify that the information	herein contained is true and	i complete to the l	best of my knowledge.
-------------------------------------	------------------------------	---------------------	-----------------------

Remarks:

By Johnny Rolinson

Deputy Oil & Gas Inspector

By Palors Sea

Title <u>Operation</u>

Date <u>6/17/98</u>

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone texts must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the eigenning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone texts: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gat-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing a temperatures (gas zones only) and gravity and GOR (oil zones only).