STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

> This form is not to be used for reporting packer leakage tests in Southeast New Mexico

> > Hour, date shut-in

Lower Completion

OIL CONSERVATION DIVISION



NORTHWEST NEW MEXICO PACKER-LEAKAGE

Well **GRENIER A** No. BURLINGTON RESOURCES OIL & GAS CO. 1A Operator Lease Location of Well: Sect Twp. 030N 010W County SAN JUAN Unit С NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD. MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper Flow Tubing FRUITLAND/PICTURED CLIFFS Gas Completion Lower Gas Artificial Tubing **MESAVERDE** Completion PRE-FLOW SHUT-IN PRESSURE DATA Length of time shut-in SI press. psig Stabilized? (Yes or No) Hour, date shut-in Upper Completion 4/16/99 72 Hours 196 Lower Completion 120 Hours 8 4/16/99 FLOW TEST NO. 1 Commenced at (hour,date)* 4/19/99 Zone producing (Upper or Lower) **UPPER** PROD. ZONE LAPSED TIME **PRESSURE** TIME TEMP REMARKS SINCE* Upper Completion Lower Completion (hour,date) 70 8 96 Hours 4/20/99 58 8 120 Hours 4/21/99 Production rate during test GOR Grav. Oil: BOPD based on Bbls. in Hours. MCFPD; Tested thru (Orifice or Meter): Gas: MID-TEST SHUT-IN PRESSURE DATA Stabilized? (Yes or No) Hour, date shut-in Length of time shut-in SI press. psig Upper Completion Stabilized? (Yes or No)

(Continue on reverse side)

Length of time shut-in

SI press. psig

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lower):		
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REN ARKS	
		Upper Completion	Lower Completio	n TEMP.		NEW ARRO
<u> </u>						
<u> </u>						
						~
	<u> </u>	<u> </u>				
Production rate du	ring test					
Oil:BOPD based onBbls. in			Hours	Grav.	GOR	
Gas:		MCFPI	D: Tested thru (O	rifice or Meter):		
Remarks:						
						-
						
	<u> </u>			the best of my knowled	lge	
Approved	OCT 13	3 1999	9	Operator Burling	ton Resources	
	il Conservation Divi			01	0.	
ar , enant , mart ,	MAL SIGNED BY CH	IARI IF T. PERRIN		By America	May	
Ву	HAT BROWER DI CI	50 Et 1/2/2019 St. 1 A		Title Operations	Associate	
DET	PUTY OIL & GAS IN	SPECTOR, DIST.	}			
Title				Date Tuesday, June 15, 1999		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and arnually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- $5. \hspace{0.5cm}$ Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: in mediately prior to the beginning of each flow period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement im nediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the b-ginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the ent re test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-g is dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec D strict Office of the New Mexico Oil Conservation Division on Northwest New Mexico Pack r Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).