

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Mesa Petroleum Co.

3. ADDRESS OF OPERATOR

1660 Lincoln St., #2800 Denver, Colo. 80264

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1830' FNL & 1795' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☒

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 03567

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gage Federal

9. WELL NO.

#3

10. FIELD OR WILDCAT NAME

Basin Dakota - Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T30N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6385' GR

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

AUG 4 1980
OIL CON. COM.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Mesa Petroleum Co. will attempt to dual complete the above well in the Dakota (7281'-7374' gross) and the Mesaverde (4550'-5262' gross).

A production packer will be set above the Dakota interval using 2 1/16" IJ tubing as the producing string. 1 1/2" NU tubing will be set to approximately 3000' to produce the Mesaverde.

RECEIVED

JUL 31 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

xc: St. of NM, TLS, Div.,
D & M, Carnes, Yoakam,
O'Connell, Conoco,
Tenneco, ELNG

Subsurface Safety Valve: Mand. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Div. Drlg. Super. DATE July 25, 1980

(This space for Federal or State office use)

APPROVED BY [Signature] 1980
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

Bruce Wamsley
for DISTRICT ENGINEER

ok 3 in
will require MV + 1, @ 5200'