

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 970°N, 1470°W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 078200 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Riddle B

9. WELL NO.
3A

10. FIELD OR WILDCAT NAME
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T-30-N, R-10-W N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6321' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☒

FRACTURE TREAT ☐ ☒

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☐

(other) ☐ ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-02-79: TD 3320'. Ran 83 jts. 7", 20#, KS intermediate casing, 3308' set at 3320'. Cemented w/377 cu. ft. cement. WOC 12 hours; held 1200#/30 min. Top of cement at 1250'.

3-05-79: TD 5600'. Ran 77 jts. 4 1/2", 10.5#, KS casing liner, 2477' set 3153-5630'. Float collar set at 5612'. Cemented w/431 cu. ft. cement. WOC 18 hours.

3-22-79: PBTD 5612'. Tested casing to 3500#, OK. Perfed Lower P.L. 5342, 5375, 5420, 5437, 5444, 5518, 5535, 5589' w/1 SPZ. Fraced w/19,500# 20/40 sand and 39,000 gal. water. Flushed w/6970 gal. water.

(OVER)

Subsurface Safety Valve: Manu. and Type Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE March 26, 1979


(This space for Federal or State office use)

APPROVED BY: [Signature] TITLE Drilling Clerk DATE March 26, 1979

CONDITIONS OF APPROVAL IF ANY

2-32-79: 101604 1122 B.T. 4070 4024 4002 2071 2021

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

3-23-79: Perfed Mass. P.L. 4949,4954,4966,5027,5034,
5052,5077,5156,5161,5184,5189,5194,5205,5214,5222,5233,
5246,5252,5258,5264,5280,5285,5290,5301,5317 W/1 SPZ.
Fraced w/70,000# 20/40 sand and 140,000 gal. water.
Fraced w/6795 gal. water. Perfed C.H.-Men: 4485,4566,
4569,4582,4588,4594,4605,4610,4615,4620,4632,4638,4644,
4658,4668,4710,4716,4722,4848,4860,4900,4916 W/1 SPZ.
Fraced w/62,000# 20/40 sand and 124,000 gal. water.
Flushed w/6527 gal. water.