

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1420' N, 810' W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE SF 078509	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME San Juan 32-9 Unit	
8. FARM OR LEASE NAME San Juan 32-9 Unit	
9. WELL NO. 33 A	
10. FIELD OR WILDCAT NAME Blanco MV	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 6, T-31-N, R-9-W N.M.P.M.	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6650' G.L.	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-14-79: Ran Bond Log and shot 1 squeeze hole at 4900'. Set RTTS packer at 4624' and squeezed w/ 207 cu. ft. cement. WOC.

7-15-79: PBTD 6186'. Tested casing to 3500#, OK. perfed 5740, 5748, 5756, 5776, 5784, 5792, 5799, 5807, 5814, 5822, 5830, 5838, 5854, 5862, 5873, 5884, 5898, 5919, 5974, 6017, 6031, 6076, 6090, 6130, 6160' w/1 SPZ. Fraced w/78,000# 20/40 sand, 161,000 gal. water. Flushed w/4100 gal water. Perfed 5058, 5164, 5292, 5306, 5366, 5389, 5397, 5404, 5410, 5418, 5427, 5504, 5534, 5542, 5550, 5627, 5666, 5680, 5688, 5698'. w/1 SPZ Fraced w/76,000# 20/40 sand, 152,000 gal water. Flushed w/3800 gal. water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. G. Duico TITLE Drilling Clerk DATE July 17, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

77MACC

Jim Lewis

