

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico 87401


4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 840'S, 1460'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON\*
- (other)

SUBSEQUENT REPORT OF



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE  
SF 078509

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
San Juan 32-9 Unit

8. FARM OR LEASE NAME  
San Juan 32-9 Unit

9. WELL NO.  
42A

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 6, T-31-N, R-9-W  
N.M.P.M.

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5599' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-27-79: PBTD 6151'. Tested casing to 3500#, OK. Perfed P.L. 5680,5686,5692,5718,5736,5746,5757,5775,5781,5795,5800,5811,5816,5831,5857,5879,5981,5988,6025,6078' W/ 1 SPZ. Fraced w/60,000# 20/40 sand, 124,092 gal. wtr. Flushed w/ 7800 gal. Wtr.

Perfed Men. & C.H. 4999,5004,5146,5302,5310,5324,5332,5346,5353,5360,5367,5374,5447,5464,5484,5502,5510,5572,5578,5624,5630,5638' W/1 SPZ. Fraced w/72,000# 20/40 sand, 145,000 gal. wtr. Flushed w/7500 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Davis TITLE Drilling Clerk DATE January 1, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MOCCI

ACCEPTED RECORD

\*See Instructions on Reverse Side

JAN 08 '80

FARMINGTON DISTRICT  
DUC