

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2001 FEB 20 PM 5:04

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

800' FNL, 1785' FWL, Sec. 17, T-31-N, R-9-W, NMPM

5. Lease Number
SF-078386

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
San Juan 32-9 Unit

8. Well Name & Number
San Juan 32-9 U#18A

9. API Well No.
30-045-23315

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Payadd	

13. Describe Proposed or Completed Operations

1-12-01 MIRU. ND WH. NU BOP. SDON.
 1-16-01 TOOH w/2 3/8" tbg. TIH w/RBP & pkr. Set RBP @ 5218'. Set pkr @ 5200'.
 PT RBP to 2500 psi, OK. PT csg to 2000 psi, failed. SDON.
 1-17-01 TOOH w/pkr. TIH w/pkr, isolate holes in csg @ 3533-3594'. SDON.
 1-18-01 (Verbal approval from Errol Becher, BLM, to squeeze). Set pkr @ 3407'.
 Pump 500 sx Class "B" cmt w/2% calcium chloride. TOOH w/pkr. SDON.
 1-19-01 ND BOP. Change out tbg head. PT tbg head to 2500 psi, OK. NU BOP. PT
 csg, failed. SDON.
 1-20-01 Pump 200 sx 50/50 Class "B" poz w/2% calcium chloride, 0.3% Halad-344,
 0.4% versaset (246 cu ft). Displace to top hole @ 3533'. WOC. Pump
 200 sx 50/50 Class "B" poz w/2% calcium chloride, 0.3% Halad-344,
 0.4% versaset (246 cu ft). SDON.
 1-22-01 TIH w/bit, tag up @ 3408'. Drill out cmt to 3607'. Circ hole clean.
 TOOH w/bit. TIH w/mill to RBP @ 5218'. Circ hole clean. SDON.
 1-23-01 (Verbal approval from Steve Mason, BLM, to run 4 1/2" tie back & patch.)
 TOOH w/mill. ND BOP. NU csg spocl. NU BOP. SDON.
 1-25-01 TIH w/86 jts 4 1/2" 10.5# J-55 csg, set @ 7403'. Lnr top @ 3704'. PT lines
 to 3000 psi, OK. Pump 50 sx 50/50 STD poz w/2% gel, 2% calcium chloride
 (61 cu ft). SDON.
 1-26-01 TIH w/bit, tag up @ 3627'. Drill out cmt to 3708'. Circ hole clean. PT csg
 to 3000 psi/15 min, OK. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 2/15/01
 TLW

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

ARMED AND DANGEROUS OFFICE
 BY [Signature]

1-27-01 TIH, tag up @ 5200'. CO to RBP @ 5218'. Spot acid. TOOH w/bit Ran CBL @ 5218-3100'. TOC @ 3386'. SDON.
 1-29-01 Perf Lewis @ 4210-4904' w/1 shct every 2', total of 60 holes. SDON.
 1-30-01 Brk dwn Lewis perfs.
 1-31-01 PT lines to 4800 psi, OK. Brk dwn Lewis perfs. Frac Lewis w/20# lnr gel, 75 quality foam, 200,000# 20/40 Brady sand. Flow back well.
 2-1-01 Flow back well. SDON.
 2-2-01 TIH, tag up @ 4831'. CO to 5203'. Blow well.
 2-3-01 Alternate blow & flow well.
 2-4-01 Alternate blow & flow well.
 2-5-01 CO to RBP @ 5218'. Blow well.
 2-6-01 CO to RBP @ 5218'. TOOH. TIH w/bailer, tag up @ 5200'. CO to 5218'. TOOH w/bailer. TIH w/retrieving head, tag up @ 5214'. CO to 5218'. Blow well.
 2-7-01 Tag up @ 5213'. CO to RBP. TOOH w/RH. TIH w/RH, tag up @ 5216'. Attempt to rotate over RBP, wouldn't latch. TOOH w/RH. SDON.
 2-8-01 TIH w/washover shoe, tag up @ 5200'. Washover to 5218'. SDON.
 2-9-01 TIH w/washover shoe, tag up @ 5208'. Washover to 5218'. SDON.
 2-10-01 Wash down to RBP @ 5218'. Latch RBP & work free. TOOH w/RBP. TIH w/mill, tag up @ 6100'. CO to PBTD. Flow well.
 2-11-01 Flow well.
 2-12-01 Tag up @ 6110'. CO to PBTD @ 6120'. TOOH w/mill. TIH w/191 jts 2 3/8" 4.7# J-55 tbg, set @ 5988'. SN @ 5984'. ND BOP. NU WH. RD. Rig released.