

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

720 S. Colorado Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1450' FNL, 1520' FEL, UNIT G

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☒  
☒  
☐  
☐  
☐  
☐  
☐

5. LEASE

USA -SF - 079511-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gartner

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 29, T30N, R8W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6190' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-11-79 - 9-13-79

MIRUCU. Installed wellhead. NU BOP. Pressure tested csg to 2000 PSI for 10 min - held ok. Spotted 300 gals double inhibited, 15% MCA acid. Ran electric log from TD to 2700'. Perforated the Pictured Cliffs formation from 2913 - 2915, 2926 - 2928, 2938 - 2946, 2952 - 2954, 2970 - 2974 w/4 JSPF, fractured well w/24,000 gals 70% foam, 1% KCL water, 30,000 # 10/20 radioactive sand. ISIP -1250 PSI, 15 min. SI -1200. ATR-20 BPM, ATP -1300 PSI. Ran electric log. Ran 1 1/4" tubing & set @ 3012'. ND BOE. RDMOCU.

Subsurface Safety Valve: Manu. and Type

Set @                      Ft

18. I hereby certify that the foregoing is true and correct

SIGNED *Carly Hatten* TITLE Admin. Supervisor DATE 9-19-79

(This space for Federal or State office use)

APPROVED BY                      TITLE                      DATE                       
CONDITIONS OF APPROVAL, IF ANY: