UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF-077482
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas gr	Holder "A"
2. NAME OF OPERATOR	9. WELL NO. #2
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesa Verde
P. O. Drawer 570, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Section 6, T30N, R12W
below.) AT SURFACE: 1450' FNL & 1300' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15 FLEVATIONS (CHOW DE LOD AND WD)
REPORT, OR OTHER BAIN	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5900' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3900 GR
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or change on Form 9,830.)
PULL OR ALTER CASING \square \square \square \square	change on Form (9-830.)
MULTIPLE COMPLETE	So. 570
CHANGE ZONES U U U U U U U U U U U U U U U U U U U	
ABANDON* \(\times\) (other)	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	rectionally drilled, give subsurface locations and
Southland Royalty Company hereby reques	ts permission to plug and
abandon this well in the following mann	er:
1. Spot 25 sx Cl "B" cement @ 4416'.	Squeeze 10 sx into perfs.
2. Pull tubing to liner top at 2200'.	Spot 10 sx of cement across
liner top and 50' above.	
3. Pull tubing out of hole.	
4. Stretch 7" casing and shoot off 50'	above free point. (Approx.
5. Spot 10 sx of cement in stub and 15	sy above
6. Spot 50' of cement above and 50' b	elow surface casing shoe.
7. Install dry hole maker with 10' sur	face plug
-	
* Note place 9.5 */gal mud Between p	105.5
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	<u>C</u>
19 I hereby cortifu that the foregoing is true and correct	

TITLE District Engine TITLE (This space for Federal or State office use) APPROVED

*See Instructions on Reverse Side

900