STATE OF NEW MEXICO **ENERGY and MINERALS DEPARTMENT** OIL CONSERVATION DIVISION. Page 1 Revised 10/01/78 be used for reporting packer leakage tests NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST in Southeast New Mexico Well Tenneco Oil Company Florance No. Operator Location of Well: Unit _L Rge. County San TYPE OF PROD. METHOD OF PROD. NAME OF RESERVOIR OR POOL - (Tbg. or Cag.) (Oll or Gas) (Flow or Art. Lift) Upper Tubina … Completio Pictured Cliff Gas Basin Dakota - Gas Flow Tubing Complette PRE-FLOW SHUT-IN PRESSURE DATA Length of time shut-in Stabilized? (Yes or No) SI press. palg iHour, date shut-in Upper 72 hrs Completion 4/22/85 309 12:10 p.m Length of time shut-in Stabilized? (Yes or No) Hour date shut-in SI press. psig . /22/85 12:10 p. 72 hrs 1354 Nο FLOW TEST NO. 1 Zone producing (Upper or Lowert | OWAY Commenced at (hour, date) * 4/25/85 8:55 a.m PRESSURE TIME LAPSED TIME PROD. ZONE SINCE* Upper Completion Lower Completion (hour, date) TEMP. 4/26/85 28. hr 309 12:35. р.п 132 4/27/85 1:25 p.m.57 hrs 324-122 JUN 03 1985 Production rate during test BOPD based on _____ Bbls. in ____ Hours. ___ Grav. __ Oil: 10 _ MCFPD; Tested thru (Orifice or Meter): _ G25: _ MID-TEST SHUT-IN PRESSURE DATA Stabilized? (Yes or No) Hour, date shul-in Length of time shut-in SI press, paig Uppe Completio Stabilized? (Yes or No) Hour, date shul-in Length of time shul-in Si press, psig

FLOW TEST NO. 2

Commenced at (hour, date) **				Zone producing (Upper or Lower):		
, TIME (nour, date)	LAPSED TIME SINCE **	PAESSURE		PROD. ZONE		
		Upper Completion	Lower Completion	TEMP.	<u>i </u>	REMARKS
		TOTTELLE	reading to	एक्स करू ५	191.00	Baran Bajaran da
	1577					,
		and the second s			†	
			•		. ±*	
Production rate d	•	D based on	•	Hours.		, GOR
Remarks:		,	rD. Tested dilu	(Office of Meter)		
•						-jæ.
I hereby certify the	at the informatio	on herein containe	NOC.	mplete to the bes		
New Mexico Oi	il Conservation D		- 17 E	- 1/.	1 - 1	-Katharine Jenkins
Ву	· · · · · · · · · · · · · · · · · · ·		т	ide Agent		,
Title DEPUTY	OIL & GAS INSPE	CTOR OICE #	I	Date 5/23/85		August 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within
 seven days after actual completion of the well, and annually thereafter as prescribed by the
 order authorizing the multiple completion. Such tests shall also be commenced on all
 multiple completions within seven days following recompletion and/or chemical or fracnute treatment, and whenever remedial work has been done on a well during which the
 packer or the tubing have been disnurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator
 small notify the Division in writing of the exact time the test is to be commenced. Offset
 operators shall also be so notified.
- 3. The packer leakage ten shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than severn days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Tent No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Procedure for Flow Ten No. 2 is to be the same as for Flow Ten No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at boutly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone teris: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Arter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).