

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1850'FSL, 860'FWL, Unit L
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Report on Completion Operations

5. LEASE
SF-078336

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Florance

9. WELL NO.
114

10. FIELD OR WILDCAT NAME
Dakota/Pictured Cliff

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11; T30N; R9W

12. COUNTY OR PARISH | 13. STATE
San Juan | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6063'GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details; and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/25-4/7/80

MIRUCU on 3/25/80. Tested csg to 3500#-held. Perf'd Dakota w/2SPF @ 7246-58, 7303-06, 7333-48, 7366-70, 7394-96, 7400-02, 7406-10, 7418-20, 7424-26, 7450-66. Acidized w/2250 gal of 15% HCL & 184 balls. Landed 2 3/8" long string @ 7200: Model F Packer @ 7200. Tested csg @ 2000#-held. Perf'd Pictured Cliff w/2 SPF @ 2855-58, 2864-66, 2869-74, 2888-96, 2901-03. Acidized w/700 gal 15% HCL & 60 balls. Frac'd w/20000 gal PAD & 30000# 10/20 sand. Flushed w/ foam. Landed short string @ 2853. Swabbed until flowing. RDMOCU on 4/7/80.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

Carley Watson

TITLE

Admin. Supervisor

DATE

4/11/80

(This space for Federal or State office use)

APPROVED BY


TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side



ACCEPTED FOR RECORD

APR 17 1980

WASHINGTON FIELD

BY *[Signature]*