

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Designation and Serial No. SF - 078336
2. Name of Operator Amoco Production Company		6. If Indian, Allottee or Tribe Name
Attention: Nancy I. Whitaker		7. If Unit or CA, Agreement Designation
3. Address and Telephone No. P.O. Box 800, Denver, Colorado 80201 (303) 830-5039		8. Well Name and No. FLORANCE #114
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1850 FSL 860 FEL Sec. 11 T 30N R 9W Unit L		9. API Well No. 3004523479
		10. Field and Pool, or Exploratory Area Basin Fruitland Coal Gas
		11. County or Parish, State San Juan New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
--------------------	----------------

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

RECEIVED
DEC 18 1996
OIL CON. DIV.

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRUSU 11/26/96

TOH LAYING DOWN TUBING. TIH AND TAGGED AT 2848'. SPOTTED CEMENT PLUG WITH 15 SXS CLASS BE NEAT, 3 BBLs FROM 2773 TO 2848' INSIDE CSG. TIH SET CIBP AT 2647'. LOADED AT PRESSURE TESTED CASING TO 500 PSI. HELD 15 MIN OK.

SPOTTED CEMENT PLUG INSIDE CSG ON TOP OF CIBP FROM 2647' TO 2447'. WITH 38 SXS, 8 BBLs OF CLASS B NEAT. SPOTTED CEMENT PLUG INSIDE CSG WITH 57 SXS, 12 BBLs OF CLASS B NEAT FROM 1584' 1884'.

SPOTTED CEMENT PLUG INSIDE 7" CASING WITH 58 SXS, 12 BBLs OF CEMENT, FROM SURFACE TO 312'.

CUT OFF WH, TOP OFF CSG W/CEMENT, AND INSTALLED MARKER.

RDSUMO 12/3/96

14. I hereby certify that the foregoing is true and correct

Signed Nancy I. Whitaker Title STAFF ASSISTANT

Date 12-16-1996

(This space for Federal or State office use)

Approved by _____ Title _____
Conditions of approval, if any:

Date _____

APPROVED

DEC 17 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false statements, or to make any materially false representations as to any matter within its jurisdiction.

NMOC

DISTRICT MANAGER