

N. OF COPIES RECEIVED **3**

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Blackwood & Nichols Co., Ltd. 3. Address of Operator P. O. Box 1237, Durango, Colorado 81301 4. Location of Well UNIT LETTER <u>M</u> , <u>830</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>31N</u> RANGE <u>7W</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 6546' GL	7. Unit Agreement Name Northeast Blanco Unit Agrmt. No. 1, Sec. 929 8. Farm or Lease Name Northeast Blanco 9. Well No. 204 10. Field and Pool, or Wildcat South Los Pinon PC 12. County San Juan
---	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08-08-79

Tested 9 5/8" casing to 800 PSI for thirty minutes; held O.K. Spudded 12 1/4" hole at 10:30 A.M., 08-08-79. Ran 5 jts 9 5/8" 36.00# H-40 casing; 204' set at 217'. Cemented with 150 sacks class B cement with 1/4# flocele per sack and 2% CaCl₂; cement circulated.

08-13-79

Ran 113 jts 4 1/2" 10.50# K-55 casing; 3675' set at 3686'. Float collar at 3635'; cemented with 265 sacks Howco Lite cement with 1/4# flocele per sack, followed with 222 sacks 50-50 Pozmix with 2% gel and 1/4# flocele per sack.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed DeLasso Loos TITLE District Manager DATE 08-14-79

Original Signed by

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: