

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Blackwood & Nichols Co., Ltd.

3. ADDRESS OF OPERATOR
P.O. Box 1237, Durango, Colorado 81301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' F/SL - 990' F/EL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM 03358

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
NEBU Agrmt. No. 1, Sec. 929

8. FARM OR LEASE NAME
Northeast Blanco Unit

9. WELL NO.
64A

10. FIELD OR WILDCAT NAME
Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
P-10-31N-7W

12. COUNTY OR PARISH: San Juan 13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6560' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-14-79 Spudded 12 $\frac{1}{4}$ " hole at 3:15 PM, 7-14-79. Ran 5 jts 9-5/8" 36.00# H-40 casing; 209.62' set at 221'. Cemented with 200 sacks class B cement; 2% CaCl₂, 1/4# flocele/sack. Cement circulated.

7-19-79 Ran 92 jts 7" 23.00# K-55 casing; 3739' set at 3726'. Cemented with 200 sacks Howco Lite cement with 1/4# flocele/sack, followed with 100 sacks of class B with 2% CaCl₂ and 1/4# flocele/sack.

7-22-79 Ran 81 jts 4 $\frac{1}{2}$ " 10.50# K-55 casing liner; 2633' set at 6188'. Float collar at 6176'; top of liner 3556'. Cemented with 300 sacks 50-50 pozmix with 2% gel, 0.6% FLA; 1/4# flocele per sack; reversed out twelve barrels cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DeJasso Loos TITLE District Manager DATE 7-23-79


(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side



JUL 24 1979

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.