

NO. OF COPIES RECEIVED	1
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator CONSOLIDATED OIL AND GAS COMPANY	8. Farm or Lease Name CLAYTON
3. Address of Operator 1860 LINCOLN STREET., DENVER, COLORADO	9. Well No. 1-E
4. Location of Well UNIT LETTER P, 875 FEET FROM THE S LINE AND 945 FEET FROM THE E LINE, SECTION 2 TOWNSHIP 30N RANGE 12W NMPM.	10. Field and Pool, or Wildcat BASIN DK
15. Elevation (Show whether DF, RT, GR, etc.) 5724' KB	12. County SAN JUAN

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 2-8-80 Drill 275' of 12 1/2" hole. Ran 1 shoe & 6 jts. 8-5/8" 24# surface casing set @ 271' and cement w/200 sacks class B neat 2% cc and 1/2 # flocele. Good cir. Cir 20 sacks to surface. Plug down 8:45 a.m. 2-8-80.
- 2-24-80 Drill 7-7/8" hole to 6868. Ran Schlumberger IES/GR, FDL/CNL logs.
- 2-24-80 Ran 174 jts. 5-1/2" 15.5# K-55 range III new casing w/stage collar @ 4740' cement 1st stage w/440 sacks 50/50 poz w/2% gel. 6/10 of 10% Halad 9 & 1/2 # flocele. Cement 2nd stage w/420 sacks 50/50 poz 2% gel. 6/10 of 1% Halad 9 & 1/2 # flocele. Had good cir. thru out. Plug down 9:30 p.m. 2-24-80



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Caryl Moore TITLE PROD. SUPT. DATE 2-27-80

APPROVED BY Caryl Moore Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE MAR 10 1980

CONDITIONS OF APPROVAL, IF ANY: