

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Supron Energy Corporation

3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 910 Ft./N; 1625 Ft./W line
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Ran Casing and Cemented

☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
JUN 12 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF 078508
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Nordhaus
9. WELL NO.
2-A
10. FIELD OR WILDCAT NAME
Blanco Mesaverde, Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11, T-31N, R-9W
N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6553 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 9-7/8" hole with mud to total depth of 3655 ft. R.K.B.
2. Ran 7-5/8", 26.40#, K-55 casing and landed at 3655 ft. R.K.B. Cemented with 250 sacks of 65-35 poz mix with 6% gel and 10 lb. of gilsonite per sack and 100 sacks of class "B" with 2% Calcium Chloride. Plug down at 5:00 P.M. 5-17-80.
3. Temperature survey showed top of cement at 1900 ft. R.K.B.
4. Drilled 6-3/4" hole with gas to total depth of 8160 ft. R.K.B.
5. Ran 5-1/2", 15.50#, K-55 casing as a liner. Bottom of liner at 8160 ft. R.K.B., top of liner at 3583 ft. R.K.B., float collar at 8145 ft. R.K.B. Cemented with 350 sacks of 50-50 poz mix with 4% gel and 150 sacks of class "B" with 0.6% water loss additive. Plug down at 4:30 P.M. 6-4-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supr. DATE June 10, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

