

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 9788
2. NAME OF OPERATOR Dugan Production Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 208, Farmington, NM 87401		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 860' FNL - 1170' FWL		8. FARM OR LEASE NAME Phil's East Job
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5628' GR		10. FIELD AND POOL, OR WILDCAT Wildcat - PC
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 4 T30N R14W
		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF
TEST WATER SHUT-OFF ☐	WATER SHUT-OFF ☐
FRACTURE TREAT ☐	FRACTURE TREATMENT ☒
SHOOT OR ACIDIZE ☐	SHOOTING OR ACIDIZING ☒
REPAIR WELL ☐	(Other) ☐
(Other) ☐	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*
- 7-10-80
Cementers Inc. squeezed perms 1030-1040' w/15 sx class "B" neat cement. Displaced cement to 800'. Squeezed 10 sx into formation. Left 230' in 2-7/8" tbg.
- 7-15-80
Southwest Surveys rigged up and perforated 14 shots 564-578' Fruitland Sand
- 7-17-80
Foam fraced Fruitland perms 564-578' w/70 quality foam. Used 69.6 bbls water, 12,600# 10-20 sand, 24 gals adafoam and 28,600 scf Nitrogen.. Max TP 1400 psi. Ave TP 1200 psi. Min 1200 psi Overall IR 20 B.M. IR of fluid 6 B/M. ISDP 600 psi - 10 min stdg pressure 500 psi.

RECEIVED

JUL 22 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE

President

DATE

7-21-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC
*See Instructions on Reverse Side

BY