NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

Lower Completion Hour, date shut-in 1:15 8/12/02

Page 1 Revised 11/16/98

Stabilized? (Yes or No)

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST Operator Energen Resources Lease FEE Well No. 3 Location of Well Unit "I" SEC 3 T30N R11W API#36045236790000

	LOCA	ation of weir	Othic	1 020 0	100,414.1	• • •	1, 1,, 0,0		
	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Oil or Gas)			METHOD OF PROD. (Flow or Art. Lift)		PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	PICTURE CLIFF			GAS			FLOW		TBG
Lower Completion	MASAVERD			GAS			INTERMENTING		TBG
		PRI	E-FLO	ow shut-l	N PRESS	UR	E DAT	Α	
Upper Completion	Hour, date shut-in 1:15 8/2/02			Length of time shut-in 73:47 HR		2	SI press. Psig TBG=199 CSG=199		Stabilized? (<u>Yes</u> or No)
Lower Completion	Hour, date shut-in 1:15 PM 8/2/02			Length of time shut-in 73:45 HR			SI press. Psig TBG=317		Stabilized? (<u>Yes</u> or No)
				FLOW T	EST NO.	1			
	hour, date)*3:00 PM 8/5/02				Zone produc	ing (<u>Upper</u> or L	.ower):	
Time (hour.date)	LAPSED TIME SENCE	PRESSURE Upper completion Lower cor			npletion	Z	PROD. REMARKS ZONE IEMP.		
7:00 am 8/6/02	16 hr	197 psii	1	81 psi		90)		
1:00 pm 8/7/02	30 hr	198 psi	1.	57 psi		90	5		
1:40 pm 8/8/02	23:40 hr	198 psi	1	76 psi		90	<u> </u>		
12:30 pm 8/9/02	23 hr	198 psi	1	61 psi		9	8		
Production Dil: 0 BE	rate during test	В	OPD	based on		[3bls. in	Hours	Grav.
GOR			–						
Gas: <u>120</u>			M	CFPD; Tes	ted thru (<u>C</u>	<u> Drifi</u>	ce or (V	leter):	
		M	ID-TE	ST SHUT-	IN PRESS	UR	E DAT	Ά	
Unner	Hour, date shut-in 1:15 8/2/02			Length of time shut-in 240 HR			SI pres	ss psig 198	Stabilized? (Yes or No)

Length of time shut-in

SI press. Psig 174

FLOW TEST NO. 2

Commence	d at (hour, date)	** 1:30 8/12/02		Zone producing (Upper or Lower):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion		PROD. ZONE	REMARKS			
":15 am 8/13/02	18.5	198 psi	304 psi	96				
1:25PM 8/14/02	30 HR	198 PSI	312 PSI	96				
1:25pm 8/15/02	24hr	198 psi	316 psi	100				
1:22pm 8/16	24hr	199 psi	316 psi	101				
Production ra	ate during test	BOPD base	d on 0 CFPD:Tested thru	Bbls. in12 u <u>(Orfice</u> or Meter	0HoursGravGOR			
Remarks: hereby certi	fy that the inforr	mation herein co	ntained is true ar	nd complete to the	e bes of my knowledge.			
Approved	il Conservation D	ි <u>?</u> 19	Operato	or <u>ENERGEN F</u>				
			By DAI	NNY BUTTON				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Date 8/16/02

Title LEASE TECH

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

By DANNY BUTTON

Title LEASE TECH

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Fow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals

during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in tripl cate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).