

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, NM 87041

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 935'S, 890'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
MAR 05 1981  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE

SF 078204

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Sunray D

9. WELL NO.  
2A (PM)

10. FIELD OR WILDCAT NAME  
Aztec PC Ext. & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21, T-30-N, R-10-W  
NMMP

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
627' GL

NOTE: Report results of multiple completion or zone change on Form 9-330.

MAR 10 1981  
OIL CON. COM.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-28-81: PBSD 5565'. Tested casing to 3500#, OK. Perfed Lower Point Lookout: 5259, 5275, 5290, 5313, 5327, 5333, 5344, 5356, 5370, 5398, 5404, 5425, 5438, 5446, 5456, 5470, 5487, 5500' W/1 SPZ. Fraced w/ 48,888# 20/40 sand, 100,000 gal. water. Flushed w/ 6678 gal. wtr. Perfed Massive Point Lookout: 5225, 5212, 5207, 5186, 5177, 5165, 5160, 5145, 5141, 5132, 5128, 5124, 5120, 5119, 5118, 5117, 5116, 5115, 5110, 5106, 5102' W/1 SPZ. Fraced w/ 27,846# 20/40 sand, 54,390 gal. wtr. Flushed w/ 6636 gal. wtr. Perfed Pictured Cliffs: 2842-2857, 2857-2972, 2884-2895, 2900-2920-2930-2942' W/12 SPZ. Fraced w/ 71,988# 10/20 sand, 76,986 gal. wtr. Flushed w/ 4830 gal. wtr. Dropped 4 sets of 12 balls each.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Buico TITLE Drilling Clerk DATE March 4, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

MAR 10 1981

FARMINGTON DISTRICT  
BY EDB