UNITED STATES DEPARTMENT OF THE INTERIOR

| | ,2 | Budget | Bureau | Nο. | 42-R142 |
|------|----|--------|--------|-----|---------|
| CACE | | | | | |

| DEPARTMENT OF THE INTERIOR | SF 078204 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | |
|---|--|--|--|
| GEOLOGICAL SURVEY | | | |
| SUNDRY NOTICES AND REPORTS ON WELLS | 7. UNIT AGREEMENT NAME | | |
| (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME | | |
| 1. oil gas D other | Sunray D 9. WELL NO. | | |
| Well — Well | 2R (PM) | | |
| 2. NAME OF OPERATOR El Paso Natural Gas Company | 10. FIELD OR WILDCAT NAME | | |
| 3. ADDRESS OF OPERATOR | Blanco PC Ext. & Blanco MV | | |
| P.O. Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 21, T-30-N, R-10-W | | |
| below.) AT SURFACE: 1065'N, 1000'E | 12. COUNTY OR PARISH 13. STATE | | |
| AT TOP PROD. INTERVAL: AT TOTAL DEPTH: | San Juan New Mexico | | |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | 14. API NO. | | |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6343' GL | | |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: | المراج المستمول | | |
| TEST WATER SHUT-OFF | (NOTE: Report results of multiple completion oc fore change on Form 9–330.) OIL CON | | |
| SHOOT OR ACIDIZE | (NOTE: Report results of multiple completion or form | | |
| REPAIR WELL U | change on Form 9–330.) | | |
| MULTIPLE COMPLETE | OIL CO 6 1930 | | |
| CHANGE ZONES | Dias Con | | |
| (other) | \ 131.3°W. | | |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine | firectionally drilled, give subsurface locations and | | |
| -14-80: TD 3291'. Ran 81 joints 20#, KS intermedd cemented w/ 402 cu. ft. cement. WOC 12 ho | ate casing 3280' set at 3291'. urs;held 1200#/30 min. Top of | | |
| cement at 2250'. | | | |
| -18-80" TD 5645'. Ran 62 joints 4 1/2", 10.5#, KE Float collar set at 5627'. Cemented w/ 4 | casing liner 2500' set 3145-5645'. 38 cu. ft. cement. WOC 18 hours. | | |
| والمنافضين | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Subsurface Safety Valve: Manu. and Type | Set @ Ft. | | |
| 18. I hereby certify that the foregoing is true and correct | | | |
| Signer A Succe Title Drilling Cl | erk pate July 28, 1980 | | |
| SIGNED 75 | | | |
| (This space for Federal or State o | | | |
| APPROVED THE THE TITLE TITLE | DATE | | |
| | | | |

AUG 05 1980

*See Instructions on Reverse Side

