

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1065'N, 1000'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
PULL OR ALTER CASING   
MULTIPLE COMPLETE   
CHANGE ZONES   
ABANDON\*   
(other)

SUBSEQUENT REPORT OF:

5. LEASE  
SF 078204

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Sunray D

9. WELL NO.  
2R (PM)

10. FIELD OR WILDCAT NAME  
Blanco PC Ext. & Blanco MV


11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21, T-30-N, R-10-W  
NMPM

12. COUNTY OR PARISH | 13. STATE  
San Juan | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6343' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-5-81: PBDT 5627'. Tested casing to 3500#, OK. Perfed Point Lookout: 5142, 5150, 5158, 5231, 5235, 5245, 5250, 5256, 5262, 5268, 5276, 5281, 5286, 5314, 5343, 5412, 5430, 5438, 5466, 5486, 5494, 5502, 5522, 5553' W/1 SPZ. Fraced w/ 74,000# 20/40 sand, 158,000 gal. wtr. Flushed w/ 6600 gal. wtr.

3-6-81: Perfed Pic. Cliffs: 2964-89, 3008-18, 3027-40, 3046-66' W/15 SPZ. Fraced w/ 76,000# 10/20 sand, 81,000 gal. wtr. Flushed w/500 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. J. Innes TITLE Drilling Clerk DATE March 16, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MMOCC

MAR 24 1981

\*See Instructions on Reverse Side

FARMINGTON DISTRICT  
BY [Signature]