

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- Infill		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name Federal Gas Com "E"
3. Address of Operator 501 Airport Drive Farmington, NM 87401		9. Well No. 1E
4. Location of Well UNIT LETTER I, 2020 FEET FROM THE South LINE AND 670 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 30N RANGE 12W NMPM.		10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5565' GL		12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> spud and set casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 13-1/2" hole on 7-13-80 and drilled to 316'. Set 9-5/8" 32.3# surface casing at 315' on 7-14-80, and cemented with 300 sx of class "B" cement containing 2% CaCl₂. Good cement was circulated to the surface. Drilled a 7-7/8" hole to a TD of 6436'. Set 4-1/2" 10.5# production casing at 6434', on 7-31-80, and cemented in two stages.

1) Used 443 sx of class "B" cement containing 50/50 Poz, 6% gel, 2# Medium tuf plug per sx, and .8% fluid loss additive. This was tailed in with 120 sx of class "B" Neat cement. Good cement was circulated to the surface.

2) Used 700 sx of class "B" cement containing 65/35 Poz, 6% gel, 2# Medium tuf plug per sx, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" Neat cement. Good cement was circulated to the surface.

The DV tool was set at 4439'.

The rig was released on 8-1-80.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By
SIGNED E. E. SYOBODA TITLE District Adm. Supvr. DATE 8-13-80

Original Signed By FRANK T. CHAVEZ SUPERVISOR DISTRICT 3 DATE AUG 1 - 1980

CONDITIONS OF APPROVAL, IF ANY: