

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

720 S. Colorado Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1030' FSL 805' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☒
☐
☐
☐
☐

5. LEASE

NM - 012647

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Riddle B

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22 T31N R 9W

12. COUNTY OR PARISH

San Juan


13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6260' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
9/18/80

Sidetrack plugs were set as follows: Plug #1: 74 sx @ 7165-6900'. Plug #2: 36 sx @ 6545-6325. Plug #3: 74 sx @ 4504-4174'. Plug #4: 50 sx @ 3680-3365'. Plug #5: 100 sx @ 3700-3460'. Ensuing operations include whipstocking blw the 7" csg. shoe @ 3481'. Wash out cmt stringer to 3700'. Circ. TOH. TIH openended set Plug 100 sx @ 3700-2935'. Tag cmt @ 3460'. Dress cmt plug to 3502'. Drill to 3540' no angle. TIH w/6 1/4" bit. Open hole to 3580' w/6 1/4" hole opener. TIH w/knuckle jt & cone head. Drill to 3602' 2 3/4". Drill to 3627', 50, TIH w/6 1/4" hole opener. Open hole from 3580-3627'. TOH w/DC. Left reamer in hole w/hole opener TIH w O/S & jars. Retrieve fish. TIH w/reamer, bit & drilling assy. Ream hole. Resume drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Carolyn M. Hutton

TITLE Asst. Div. Admin. Mgr DATE September 29, 1980

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY 1000

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FARMINGTON DISTRICT

NMOCC

BY

BW