Form 9-331 Dec. 1973

Form A	pproved			
Budget	Bureau	No.	42_R143	,

UNITED STATES	Budget Bureau No. 42-R14
DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	NM-012647
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	
1. oil gas	8. FARM OR LEASE NAME
well well other	Riddle B
2. NAME OF OPERATOR	9. WELL NO.
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P.O. Box 3249, Englewood, CO 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY (AREA
AT SURFACE: 1030' FSI, 805' FWI	Sec. 22 T31N R9W
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	AT AT NO.
METORY, OR OTHER DATA	15. ELEVATIONS (SHOW DE KOR AND W
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6260 gr.
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE	
REPAIR WELL	En 1 May
PULL OR ALTER CASING AND	Enote: Report results of multiple completion or zoichange on Form 9-330.)
ABANDON*	
ABANDON* (other) csg. report U. S. GEOLOGICAL SI FARMINGFON, N.	JRVEY
17. DESCRIBE PROPOSED OR COMPLETED OPENING	<u>d. </u>
including estimated date of starting any proposed work. If well is dir measured and true vertical depths for all markers and zones pertinent	ectionally drilled, give subsurface locations an
10/8/80	to this work.)*
P	
Run 20 jts. 11.6# & 89 jts. 10.5# $4\frac{1}{2}$ " csg Run 112 jts. (3478') of $4\frac{1}{2}$ " 10.5# csg N/Reven	• Set @ 7708. TOT. @ 32901
Run 112 jts. (3478') of $4\frac{1}{2}$ " 10.5# csg. w/Bowen together set csg. slips w/80,000#. Drill out	Csg. patch. Tie string back
together set csg. slips w/80,000#. Drill out circulate backside of csg. Not successful m	latch collar. Attempt to
Establish circulation through	TH W/perf gun. Perf @ 7680.
Establish circulation through perfs. Cmt w/150 down 7" x 4½" annulus from top. Finish TIH w/2 KB. Release rig 10/13/80.	Osx 50/50 POZ mix w/6% gel
KB. Release rig 10/13/80.	2-3/8" tbg. land @ 7664'
Subsurface Safety Valve: Manu. and Type	Sat @
18. I hereby certify that the toregoing is frue and correct	
Take 1	gr_ date10-22-80
(This space for Federal or State office	
APPROVED BY	
CONDITIONS OF APPROVAL, IF ANY:	DATE